



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

RXSOL-10-1102-020

Degreaser Bio Degradable - 20 Ltrs

Material Safety Data Sheet (MSDS)

1. Product and Company Identification

www.rxmarine.com

Product Name	TSP Solution
Product Code	RXSOL-19-1522-050

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

STOCK POINT : Mumbai, Chennai, Visakhapatnam, Kandla, Kolkata, Fujairah

Phone	+91 22 27815541 / 42
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Chemical Name	Cas No
TSP Solution	7601-54-9

Synonym (s).....Sodium orthophosphate dodecahydrate

3. Hazards Identification

www.rxmarine.com

Potential Health Effects:-

Inhalation	Material is irritating to mucous membranes and upper respiratory tract. Exposure can cause coughing, chest pains and difficulty breathing.
Ingestion	May cause burns of the mouth, throat and stomach. Aspiration into the lungs may occur during ingestion or vomiting, resulting in lung injury. Symptoms may include bleeding, vomiting diarrhoea, fall in blood pressure. Damage may appear days after exposure.
Skin Contact	Material is irritating to mucous membranes and upper respiratory tract. Exposure can cause coughing, chest pains and difficulty breathing.
Eye Contact	May cause eye burns. May cause permanent corneal injury. May cause severe eye irritation. Corrosive! Causes irritation of eyes, and with greater exposures, it can cause burns that may result in permanent impairment of vision, even blindness.

4. First Aid Measures

www.rxmarine.com

Inhalation	Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
Ingestion	Do Not Induce Vomiting! Give large quantities of water or milk if available. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Skin Contact	Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician, immediately. Wash clothing before reuse.
Eye Contact	Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. Fire-fighting Measures

www.rxmarine.com

Fire	Not considered to be a fire hazard. The hot or molten material can react violently with water. Can react with certain metals, such as aluminium, to generate flammable hydrogen gas.
Explosion	Not considered to be an explosion hazard.
Fire Extinguishing Media	Use any means suitable for extinguishing surrounding fire. Adding water to caustic solution generates large amounts of heat.

6. Accidental Release Measures

www.rxmarine.com

Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. Residues from spills can be diluted with water, neutralized with a dilute acid such as acetic, hydrochloric or sulfuric. Absorb neutralized caustic residue on clay, vermiculite or other inert substance and package in a suitable container for disposal.

7. Handling and Storage

www.rxmarine.com

Keep in a tightly closed container. Protect from physical damage. Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities. Always add the caustic to water while stirring; never the reverse. Containers of this material may be hazardous when empty since they retain product residues (dust, solids); observe all warnings and precautions listed for the product. Do not store with aluminum or magnesium. Do not mix with acids or organic materials.

8. Exposure controls and personal protection

www.rxmarine.com

Airborne Exposure Limits	OSHA
OSHA Permissible Exposure Limit (PEL)	2 mg/m ³ Ceiling – ACGIH

Threshold Limit Value (TLV)	2 mg/m3 Ceiling
Ventilation System	A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.
Personal Respirators	If the exposure limit is exceeded, a half-face dust/mist respirator may be worn for up to ten times the exposure limit or the maximum use concentration specified by the appropriate regulatory agency or respirator supplier, whichever is lowest. A full-face piece dust/mist respirator may be worn up to 50 times the exposure limit, or the maximum use concentration specified by the appropriate regulatory agency, or respirator supplier, whichever is lowest. For emergencies or instances where the exposure levels are not known, use a full-facepiece positive-pressure, air-supplied respirator.
WARNING	Air-purifying respirators do not protect workers in oxygen-deficient atmospheres.
Skin Protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.
Eye Protection	Use chemical safety goggles and/or a full face shield where splashing is possible. Maintain eye wash fountain and quick-drench facilities in work area.

9. Physical and chemical properties

www.rxmarine.com

Appearance	Clear to opeque
Odor	Odorless
Solubility	100%
pH	11.8 (1% Solution @ 25°C)
% Volatiles by volume @ 21C (70F)	0
Boiling Point	1390C(2534F)
Melting Point	318C(604 F)
Vapor Pressure (mm Hg)	Negligible
Evoporation Rate (BuAc = 1)	No information found
Molecular Weight	380.13

10. Stability and reactivity

www.rxmarine.com

Stability	Stable under ordinary conditions of use and storage. Very hygroscopic. Can slowly pick up moisture from the air and react with carbon dioxide from air to form sodium carbonate.
Hazardous Decomposition Products	Decomposition by reaction with certain metals releases hydrogen gas.
Hazardous Polymerization	Will not occur.

Incompatibilities	Contact with nitromethane and other similar nitro compounds causes the formation of shock-sensitive salts. Contact with metals such as aluminium, tin, and zinc causes the formation of flammable hydrogen gas.
Conditions to Avoid	Moisture, dusting and incompatible.

11. Toxicological information

www.rxmarine.com

Skin Irritation	Irritant wash with soapy water
Eye Irritant	Moderate irritant, flush with copious amounts of water
Sensitization	Not Sensitizing.

(All above information as per data available with us)

12. Ecological information

www.rxmarine.com

Comment	Not applicable
Ecotoxicity	Fish Toxicity..... EC50(96hr, Mosquitofish): 151mg/L Biodegradability..... The resulting phosphate
Environmental Effects	Not available
Do not allow the product to reach drinking water soil.	

13. Disposal considerations

www.rxmarine.com

This material must be disposed with local national regulations. Product Recommendation (Recommended cleaning agent: water) Can be burnt under adherence to the necessary technical regulations. Disposal must be made according to official regulations.Can be reused or recycled after cleaning .

14. Transport information

www.rxmarine.com

- Transport/Additional information

Land transport ADR/RID (cross-border)

ADR/RID class: -

Maritime transport IMDG:

IMDG Class: - **Marine pollutant**: No

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: - TDG

15. Regulatory information

www.rxmarine.com

- Irritating to eyes and skin.
 - Safety phrases
- 2 Keep out reach of children
If swallowed, seek medical attention immediately
22 Harmful if swallowed
26 In case of contact with eyes, rinse immediately with plenty of water and

seek medical attention.

27 After contact with skin, wash immediately with plenty of water and soap and rinse thoroughly.

- National regulations

16. Other information

www.rxmarine.com

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. Department issuing data specification sheet Environment protection department. Note: No Environmental Problems Are Expected If The Product Is Handled Correctly.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.