



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

RXSOL-15-1017-005

Gum Adhesive Remover

Material Safety Data Sheet (MSDS)

1. Product and Company Identification

Product Name	STICK N SOL - Removing Label
Product Type	RXSOL-35-1017-005

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

BRANCH STOCK POINT : Mumbai, Kandla, Chennai, Visakhapatnam, Chennai, Kolkata, Fujairah, Muscat, Nairobi, Canada

Phone	+91 27815541 / 42
Fax	+91 22 2781 1318 ::::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / information on ingredients

PRINCIPLE HAZARDOUS INGREDIENTS:	OSHA PEL
Glycol Ether DB (CAS # 112-34-5)	N/A
Acetone (CAS # 67-64-1)	1000 p.p.m.
Isopropyl Alcohol (CAS # 67-63-0)	400 p.p.m.
Orange Oil (CAS # 5989-27-5)	N/A
Proprietary	N/A

3. Hazards Identification

Route(s) of entry Eyes: yes Skin: Yes Inhalation: Yes Ingestion: Yes

Health Hazards: Eyes – May cause irritation.

Skin – May cause irritation.

Inhalation – Excessive exposure may cause respiratory irritation

Ingestion – Large amounts may be harmful

Carcinogenicity: NTP: Known – No; Anticipated – No OSHA: TLVA4 for Acetone & Isopropyl Alcohol IARC: No

4. First Aid Measures

Eyes: Flush thoroughly with water for 15 minutes. Get medical attention.

Skin : Flush thoroughly with water for 15 minutes. Get medical attention.

Inhalation: Move to fresh air. Get medical attention if irritation occurs.

Ingestion: Do not induce al vomit unless directed to do so by medical personnel. Get medical attention if irritation occurs.

5. Fire-fighting Measures

Boiling Point: 178 ° F

Extinguishing Media: Use water, carbon dioxide, dry powder or other media appropriate for materials actually involved in fire.

Special Fire Fighting Procedures: In the event of a fire, wear full protective clothing and NIOSH-approved, self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

Unusual Fire and Explosion Hazards: None

6. Accidental Release Measures

SMALL SPILL: Absorb liquid on inert material such as vermiculite, and dry sand.

LARGE SPILL: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, contain area of spill to prevent spreading, pump liquid to salvage tank. Remaining liquid may be absorbed with inert material such as dry sand, vermiculite, and shoveled into containers. Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify the proper authorities as required that a spill has occurred.

7. Handling and Storage

Store out of reach of children. Keep container tightly closed as acetone tends to volatize out of even sealed bottles over time. . Store in a cool, dry location. Avoid freezing or extended storage in high temperatures.

8. Exposure controls and personal protection

Airborne Exposure Limits: None established.

Ventilation System: Room ventilation is normally satisfactory. Mechanical assist may be required when vapors or mist are generated.

Personal Respirators: For conditions of use where exposure to dust or mist is apparent and engineering controls are not feasible, a particulate respirator (NIOSH approved) may be worn.

Skin Protection: Wear protective gloves and clean body-covering clothing.

Eye Protection: Use chemical safety goggles.

9. Physical and chemical properties

Odor :	Orange
Physical State:	Liquid.
Appearance:	Clear
pH :	N/A
Specific Gravity:	0.912 g/mL
Boiling Point:	182 ° F
Freezing/Melting Point:	N/E
Vapor Pressure:	N/E
Vapor Density:	N/E
Solubility in Water:	Miscible

10. Stability and reactivity

Stability: Stable under ordinary conditions of use and storage.

Hazardous Decomposition or Byproducts: Exposure to fire may liberate carbon dioxide, carbon monoxide, and other unidentified thermal decomposition products from this product or its packaging.

Hazardous Polymerization: Will not occur.

Incompatibilities: Acid materials and strong oxidizing materials.

Conditions to Avoid: None known

11. Toxicological information

Acetone - Oral Rat LD50: 5800 mg/kg. Inhalation Rat LC50: 100 mg/m³, irritation eye rabbit, standard draize, 20 mg severe; investigated as a tumorigen, mutagen, reproductive effector.

Glycol Ether DB -Oral Rat LD50: 7,292 mg/kg Dermal Rabbit LD-50: 2,764 mg/kg

Skin Irritation (rabbit) slight Eye Irritation (rabbit) moderate

12. Ecological information

Environmental Fate: .Readily biodegrades.

Environmental Toxicity: Glycol Ether DB Acute Aquatic

Effects Data: 24 h LC-50 (goldfish): 2700 mg/L 96 h LC-50 (bluegill sunfish): 1300 mg/L

13. Disposal considerations

Do not dispose of on the land, in surface waters, sewers or in storm drains. Larger quantities should be collected for reuse or consigned to a

licensed hazardous waste hauler for disposal in accordance with federal, state and local regulations. All disposal must be in accordance with all

federal, state and local regulations.

14. Transport information

Ground Transportation: Limited quantity exception applies for each box containing 12 pints. Requires a limited quantity label.

Air Transportation: With a vented seal/cap, this item cannot be shipped via air in accordance with CFR 49 173-24(g).

Maritime Transportation: Non Flammable Liquid
Check regulation for limited quantity exceptions.

15. Regulatory information

Glycol Ether DB (CAS # 111-76-2) SARA 313

Isopropanol (CAS #67-63-0 <2%) MASS, NJHS, NRC, OSHAWAC, PA, SARA 313,
TXAIR, WHMIS 1%

All components are listed on TSCA

CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act

MASS = Massachusetts Hazardous Substance List

NJHS = New Jersey Right-to-Know Hazardous Substances

NRC = Nationally Recognized Carcinogens

OSHA WAC = OSHA Workplace Contaminants

PA = PA Right-to-Know List of Hazardous Substances

SARA 313 = SARA 313 Title III Toxic Chemicals

TXAIR = Texas Air Contaminants with Health Effects Screening Level

WHMIS = Workforce Hazardous Material Information System

16. Other information

This product has no established regulatory information. All regulatory information given is based on individual components of the mixture by component number. While this information and recommendations set forth herein are believed to be accurate and reliable, it is provided without warranty regarding its accuracy.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit varanasichemical.com. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but

does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.