



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

Material Safety Data Sheet (MSDS)

RXSOL-16-1698-025

Pickling Inhibitor RXSOL 31 A

1. Product and Company Identification

Product Name	RXSOL-16-1698-025
Product Type	Pickling Inhibitor RXSOL 31 A
HS CODE	34029019

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Gandhidham, Chennai, Visakhapatnam, Fujairah, Muscat, Nairobi

Phone	+91 22 27815540 / 41 / 42
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / information on ingredients

Hazardous components	CAS NUMBER	%
Pyridine, alkyl derivatives	Proprietary	30 - 60
1,3-Diethyl-2-thiourea	105-55-5	10 - 30
Sulfuric acid	7664-93-9	10 - 30
Alkylphenol Ethoxylate	Proprietary	1 - 5
Proprietary Blend	Mixture	10-20

3. Hazards Identification

	EMERGENCY OVERVIEW
	HMIS:
Physical state: Liquid	HEALTH: *3

Color: Dark brown	FLAMMABILITY: 0
Odor: Pungent	PHYSICAL HAZARD: 1
	Personal Protection: See MSDS Section 8

DANGER-CORROSIVE!: CAUSES EYE, SKIN AND RESPIRATORY TRACT BURNS. POSSIBLE CANCER HAZARD.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Mists, vapors or liquid may cause severe irritation or burns. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.

Skin contact: Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation and burns. This product may cause an allergic skin reaction. A component in this product may be absorbed through the skin in harmful amounts.

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.

Ingestion: This product may produce corrosive damage to the gastrointestinal tract if it is swallowed. May cause dizziness, incoordination, headache, nausea, and vomiting.

Existing conditions aggravated by exposure: Eye, skin and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). See Section 11 for additional toxicological information.

4. First Aid Measures

Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
Skin contact:	Remove contaminated clothing and footwear. For skin contact flush with large amounts of water. If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Notes to physician:	Treat symptomatically and supportively.

5. Fire-fighting Measures

Flash point:	Not applicable
Autoignition temperature:	Not applicable
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable

Extinguishing media:	Use media appropriate for surrounding material.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	This product is an aqueous mixture which will not burn. May react with metals to form flammable hydrogen gas.
Hazardous combustion products:	Irritating and toxic gases or fumes may be released during a fire. Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. Accidental Release Measures

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Eliminate all sources of ignition or flammables that may come into contact with a spill of this material.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. Handling and Storage

Handling:	Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. For industrial use only. NEVER ADD WATER TO PRODUCT. For dilutions, add product slowly to water while stirring. Use caution; heat may be generated.
Storage:	For safe storage, store between 14 °F (-10°C) and 104 °F (40°C) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. Exposure controls and personal protection

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Pyridine, alkyl derivatives	None	None	None	None
1,3-Diethyl-2-thiourea	None	None	None	None
Sulfuric acid	0.2 mg/m ³ TWA Thoracic fraction.	1 mg/m ³ TWA	None	None
Alkylphenol ethoxylate	None	None	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

9. Physical and chemical properties

Physical state:	Liquid
Color:	Clear
Odor:	Pungent
Odor threshold:	Not available.
pH:	< 2
Vapor pressure:	Not determined
Boiling point/range:	> 100 °C (> 212°F)
Melting point/ range:	-23 °C (-9.4 °F)
Specific Gravity:	1.03 - 1.06 at 60 °F (15.56 °C)
Vapor Density:	Not determined
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Complete
Partition coefficient (n-octanol/water):	Not determined
VOC content:	Not applicable
Viscosity:	223 cp

10. Stability and reactivity

Stability:	Stable at normal conditions.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	Keep away from organic, alkaline, and oxidizing materials, metallic powders, chromates, chlorates, nitrates, and carbides.
Conditions to avoid:	Store away from incompatible materials.

11. Toxicological information

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Pyridine, alkyl derivatives	No	No	No
1,3-Diethyl-2-thiourea	No	No	No
Sulfuric acid	Known To Be Human Carcinogen.	Group 1	No
Alkylphenol ethoxylate	No	No	No

Hazardous components	Health Effects/Target Organs
Pyridine, alkyl derivatives	No Target Organs
1,3-Diethyl-2-thiourea	Irritant, Allergen
Sulfuric acid	Carcinogen, Corrosive, Irritant, Lung
Alkylphenol ethoxylate	Irritant

12. Ecological information

Ecological information: Not available.

13. Disposal considerations

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: This product, if discarded directly, would be a characteristic RCRA corrosive waste (D002).

14. Transport information

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Sulfuric acid

Hazard class or division: 8

Identification number: UN 2796

Packing group: II

DOT Reportable quantity: Sulfuric acid

International Air Transportation (ICAO/IATA)

Proper shipping name: Sulphuric acid

Hazard class or division: 8

Identification number: UN 2796

Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: SULPHURIC ACID

Hazard class or division: 8

Identification number: UN 2796

Packing group: II

15. Regulatory information

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: Sulfuric acid (CAS# 7664-93-9).

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health, Reactive

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Sulfuric acid (CAS# 7664-93-9).

CERCLA Reportable quantity: Sulfuric acid (CAS# 7664-93-9) 1,000 lbs. (454 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

WHMIS hazard class: D.1.B, D.2.A, D.2.B, E

16. Other information

This material safety data sheet contains changes from the previous version in sections: This Material Safety Data Sheet contains changes from the previous version in Section(s): 1, 2, 3, 7, 8, 9, 11, 13 & 15.

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, RX MARINE INTERNATIONAL does not assume responsibility for any results obtained by persons over whose methods RXSOL has no control. It is the user's responsibility to determine the suitability of RXSOL's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any RXSOL's products. In light of the foregoing, RXSOL specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of RXSOL's products. RXSOL further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable.

However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.