



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

Material Safety Data Sheet (MSDS)

RXSOL-16-1747-025

LIME Marine Water Scale Remover

1. Product and Company Identification

www.rxmarine.com

Product Name	LIME Marine (Marine Water Scale Remover)
Product Type	RXSOL-16-1747-025

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Kolkata, Visakhapatnam, Chennai, Hazira, Fujairah, Muscat, Nairobi

Phone	+91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax	+91 22 2781 1318 ::::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

MATERIAL OR COMPONENT	TLV (p.p.m.)	PEL (p.p.m.)	APPROXIMATE %
HYDROGEN CHLORIDE, AQUEOUS	5	5	LESS THAN 10
Inhibitor Proprietary Blend	...	...	More then

40

3. Hazards Identification

www.rxmarine.com

Threshold Limit Value:	:None For Total-Material Is An Aqueous Organic Salt Solution And As Such Has Little Vapor Pressure And No Noxious Fumes.
Effects Of Overexposure	:Should Not Be Considered Hazardous When Used As Directed.
Emergency & First Aid	:If Eye/Skin Contact, Copious Water Rinse. Consult Physician. Not To Be Taken Internally. If Ingested-Do Not Induce Vomiting-Drink Milk, Egg Whites, Etc. As Directed By Physician.

Note: Adverse Effects On Human Health Are Not Expected From The Lime Marine Solution.

4. First Aid Measures

www.rxmarine.com

Contact with skin: Remove contaminated clothing immediately and drench affected skin with plenty of water. Then wash with soap and water. When in doubt or symptoms persist, seek medical attention. Contaminated clothing should be laundered before reuse.

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes. Irrigate eyes thoroughly whilst lifting eyelids. Seek immediate medical attention. Continue flushing with water until medical help arrives.

Ingestion: Never make an unconscious person vomit or drink fluids. Give plenty of water to drink. Do not induce vomiting. Seek immediate medical attention.

Inhalation: Remove patient to fresh air. Keep warm and at rest, in a half upright position. Loosen clothing. When in doubt or symptoms persist, seek medical attention.

General: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) (S45).

5. Fire-fighting Measures

www.rxmarine.com

FLASH Point: No Flash Point, Extinguishes Flame

Extinguishing Media: Does Not Support Combustion

Special Fire Fighting Procedures: None-Water Will Control, Or Co2/Dry Chemicals

Unusual Fire & Explosion Hazards: Non-Combustible Or Explosive. Breathing Apparatus Recommended

6. Accidental Release Measures

www.rxmarine.com

Personal Precautions: Wear protective clothing as per section 8. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.

Environmental Precautions: Do not allow to enter public sewers and watercourses.

Immediate Actions: Use appropriate containment to avoid environmental contamination (S57).

Clean Up Actions: Absorb spillage in inert material and shovel up. Ventilate the area and wash spill site after material pick-up is complete.

Special Precautions: Wear protective clothing as per section 8. Avoid release to the environment. Refer to special instructions/Safety data sheets (S61). Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.

7. Handling and Storage

www.rxmarine.com

Ventilation:

1. Local Exhaust:	Normal
2. Mechanical:	Sufficient
3. Respiratory:	None

Protective Gloves: Recommended, Such As Neoprene Gloves.

Eye Protection: Recommended, Such As Chemical Goggles.

Other Protective Equipment: As Recommended By Plant Safety Department. To

revent Staining Of Clothes, Wear An Apron.

8. Exposure controls and personal protection

www.rxmarine.com

Action To Take For Spills: Rinse With Copious Amounts Of Water To Dilute: Sodium Bicarbonate May Also Be Used To Soak Up And Neutralize Liquid.

Disposal Method: Expended Or Used Material May Be Disposed Of Down Sewer With Water Flush. Material Is Biodegradable-Even As Received

9. Physical and chemical properties

www.rxmarine.com

Boiling Point: ° C.	105
Solubility In Water:	Miscible
Specific Gravity, (Water=1):	1.03 @ 25 Degreec
Vapor Pressure:	20.1mmhg @ 25 Degree C
Vapor Density, (Air=1):	.62 @ 25 Degree C
Percent Volatile By Volume:	~99.0%
Appearance:	Dark Liquid
Odor:	Roasted Almonds
Ph:	Unreadable, Generally < 3
Evaporation Rate, (Water=1):	Slow
Physical State:	Liquid

10. Stability and reactivity

www.rxmarine.com

- This article is considered stable under normal conditions, May cause rubber to swell
- Avoid overheating
- Incompatible with strong oxidizing substances, Contact with alkaline earth metals may form explosive gases, Contact with alkali metals may form explosive gases
- See Section 5

11. Toxicological information

www.rxmarine.com

Contact with skin: In cases of severe exposure, redness and irritation may develop

Contact with eyes: Causes severe irritation

Ingestion: May cause gastro-intestinal disturbances

Carcinogenicity: No evidence of carcinogenic effects

12. Ecological information

www.rxmarine.com

Handling And Storing: Preserve Integrity Of Container.

Can Material Be Stored Outside? Yes, Maintain Temperature Between 10°-180° F.
Is Material Freezable? Yes. < 0° F

13. Disposal considerations

www.rxmarine.com

Classification: This material and/or its container must be disposed of as hazardous waste EU Waste class
Disposal considerations Do not discharge into drains or the environment, dispose to
anauthorised waste collection point Disposal should be in accordance with local, state or
national legislation.

14. Transport information

www.rxmarine.com

Not classified as a hazardous for transport

15. Regulatory information

www.rxmarine.com

Stability:	Table
Incompatibilities:	Trong Caustics
Hazardous Decomposition Products:	None
Hazardous Polymerization:	Will Not Occur
Conditions To Avoid:	Excessive Heating

16. Other information

www.rxmarine.com

Text of R and S phrase codes used in this safety data sheet:-

R34 Causes burns;

R36 Irritating to eyes;

R37 Irritating to respiratory system;

R41 Risk of serious damage to eyes.

The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other appli-cation(s) without seeking advice from manufacturer.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit varanasichemical.com. This

document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.