



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

RXSOL-16-2020-030

RXSOL ORG - 1

Material Safety Data Sheet (MSDS)

1. Product and Company Identification

www.rxmarine.com

Product Name	:	RXSOL-16-2020-030
Product Type	:	RXSOL ORG1

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	:	+91 22 65113333 / 5555 / 9999 / 27611360
Fax	:	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	:	mail@rxmarine.com , sales@tankcleaner.net/
Website	:	www.rxmarine.com/ , www.tankcleaner.net/

2. Composition / Information on ingredients

www.rxmarine.com

Chemica Name	Concentration	CAS Number	EC Number	R Phrases*	Symbols Disodium
Hydrogenated Mixture					
organic solvents					
Fatty Alcohol Ethoxylate					

Mixture of the substances listed below with no hazardous additions.

Hydrogenated Mixture of C10-C13 organic solvents : Xn,65

Symbol: Xn, N

Fatty Alcohol Ethoxylate 34398-01-1 1 - 5 Xi,36/38

10-25% No Hazardous additionsz

Xn=Harmful, Xi=Irritant, N=Environmentally Harmfull

3. Hazards Identification

www.rxmarine.com

Human Health Hazards R 36/38	Causes Irritation / Inhalation may cause headache & dizziness . may cause adverse effects to aquatic environment. Keep away from food, children , animal .
------------------------------	---

4. First Aid Measures

www.rxmarine.com

INHALATION	supply fresh air on irritation medical attention require & show this MSDS to physician.
SKIN contact	In case of contact with skin , wash immediately with plenty of water and soap Remove contaminated clothes. On extra irritation use ointment on Doctor advice.
EYE contact	Flush with running water on open eyelids for at least 15 minutes, Immediately medical attention require.
INGESTION	seek medical attention , don't try to drink more water / milk because too much water increase the danger of vomiting . (on vomiting always keep head low to prevent inhalation of airways)

5. Fire-fighting Measures

www.rxmarine.com

Suitable Water , fog or mist, alcohol-resistant foam, on small fires dry chemical, carbon dioxide (CO2) also can used.
Not suitable Alcohol foam / and high pressure of water jet may cause splitting of excess materials.
Special container close to fire cooled immediately then remove to other place.
Precaution for fire-fighters Self contained breathing apparatus or apparatus should attached to air supply.
NOTE : fired materilas vapours are heavier than air and may travel along the ground for to ignition sources , so try to move all sources to safe distance otherwise keep in cooling mode.

6. Accidental Release Measures

www.rxmarine.com

ENVIROMENTAL PRECAUTION	Direct flow into drainage system, surface or ground water is prohibited.
CLEANING METHOD	for preventing the spreading of materials remove spill mechanically or with absorbent materials and dispose of in accordance with section 13.Flush with large amounts of water to clean the area.Ventilate well.
Personal	During usage of chemical personal should use all normal protective equipment and avoid contact with eye and skin and for use in close environment personnel should use respiratory breathing apparatus.

7. Handling and Storage

www.rxmarine.com

Condition to Avoid	Flammable but product is stable under normal condition , take precaution as industrial chemical .
Materials to Avoid	Do not subject directly to ALKALINE / Acidic medium.
Handling Keep Container Tightly Closed in the original container and keep away from open flames / ignition sources	
NOTE :Eyewash facilities require at workplace - The product causes corrosion on skin and mucous membranes GENERALLY Pl. Note that In case of discharge of acidic or alkaline products into the sewerage system the pH must be in the range of 6-10 since higher or lower pH values may damage the sewerage system or impair biological dosage treatment plants. So that for maintaining pH we have to add acidic / basic medium neutraliser . For example if pH is less than 6 basic neutraliser is required and if pH is more than 10 acidic nature neutraliser is required. For details of any guideline pl. Visit our technical website www.rxmarine.com • Dilute in water (always use plastic jar and RXSOL should be added to water never add water to RXSOL.)	

8. Exposure controls and personal protection

www.rxmarine.com

Personal protection	
Respiratory System Protection	Approved respirator must be worn when spraying otherwise normally not required
Eye Protection	if there is possibility to contact wear goggles for eye protection
Hand protection	wear PVC chemical resistance protective gloves
Other Information	smoking in store / work area is prohibited.

9. Physical and chemical properties

www.rxmarine.com

APPEARANCE	Clear brownish liquid
DENSITY	g/cm ³ at 15°C: 0.89
pH	NA
FLASH POINT	90 °C
Boiling point	210 °C
Ignition temp	N/A
SOLUBILITY	Emulsifiable with water / soluble in most solvents

10. Stability and reactivity

www.rxmarine.com

Stable under normal condition on access of heat Vapour/gas may form explosive mixtures with air.	
Hazardous Decomposition Products	No decomposition if stored and used as directed. In FIRE combustion CO, CO ₂ , NH ₃ , SOX etc hazardous gas produced.
NOTE	AVOID CONTACT WITH ALKALINE SUBJECT / high temperature / fire .
Note	MATERIALS TO AVOID Hydrocarbons and their derivatives may attack certain types of plastic, rubber and paint.

11. Toxicological information

www.rxmarine.com

Skin Irritation	Gives irritation may causes dryness. And prolonged contact with skin can cause degreasing effect.
Eye Irritat	Cause severe irritation
Sensitization	Sensitizing properties not known
Chronic Toxicity	Not Identified
Carcinogenicity	Not regulated. (prolonged inhalation of solvents may cause chronic solvent intoxication.

12. Ecological information

www.rxmarine.com

RXSOL OB 1005 emulsifies in water and degradable , Toxic to aquatic organism & dangerous for environment but no enviromental problem will create when the product is used correctly . in its intended use the product will not be released into the environment.

13. Disposal considerations

www.rxmarine.com

As per guide line of local rules and regulation and before disposal and neutralization pl. refer 07 article..

14. Transport information

www.rxmarine.com

Goods classified for road / rail / sea transport : YES with UN-no: : 3082
 Proper shipping name: Environmentally hazardous liquid: contains (Alkyl (C3-C8) Benzenes)
 Hazard identification no.: 90 Product identification (UN) no.: 3082
 TREMCARD no. CEFIC: 90G01
 Marine pollutant: Yes
 Flash point : 90 °C
 Labelcolour : White./Black.

15. Regulatory information

www.rxmarine.com

Symbols	Xn, N
Contains	Aromatic Hydrocarbons, Alkyl (C3-C8) benzenes

R-phrases	R-51/53 Toxic to aquatic organisms/may cause long term adverse effects in the Environment R-52 Marine Pollutant
R-65 Harmful	May cause lung damage if swallowed
S-phrases	S-23 Do not breathe vapour S-24 Avoid contact with skin S-60 This material and its container must be disposed of as hazardous waste S-61 Avoid spillage to the environment. Ask for special instructions/safety
Datasheet	S-62 If swallowed, do not induce vomiting; seek medical advice immediately S-36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
REFERENCES	Classified according to European directive on classification of dangerous preparations 90/492/EEC and accordance with EU directive 88/379. .

16. Other information

www.rxmarine.com

on the basis of information and experience as well as our present knowledge this guidelines is only safe for handling, use, processing, storage, transport, disposal and discharge; this is not a guarantee or quality of specification. And combination with other products will lost the properties. It is always the responsibility of the user to take all necessary steps to ensure that information given here is read and understood by all who use, handle, dispose of or in any way come in contact with the product.

It is not to be considered as a guarantee of the products properties. Disclaim::: The information in this MSDS is meant as a description of the safety requirements of our product.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit varanasichemical.com. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.