RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

Material Safety Data Sheet (MSDS)

RXSOL-19-1252-210
Butyl Cellosolve Acetate

1. Product and Company Identifaction

Product Name	Butyl Cellosolve Acetate
Part Number	RXSOL-19-1252-210

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone	+91 22 20871200 - 1400
Fax	+91 22 27612100 :::AOH :0091 9821214367
Email	mail@rxmarine.com
Website	www.rxmraine.comA

2. Composition / informationon ingredients

Chemical Name	CAS	EC number	Weight
Butyl Cellosolve Acetate	Butyl cellosolve acetate	--	<= 100 %

3. Hazards Identification

Signal Word	Warning
Hazard Statements	Combustible liquid. Harmful if swallowed or in contact with skin. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements	Keep away from flames and hot surfaces. - No smoking. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. In case of fire: Use water fog, dry chemical, CO2 or 'alcohol' foam to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations
Classification of the substance or mixture	Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.
Supplemental Hazard Statements	None.
Other hazards	Other hazards which do not result in classification: : Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Direct skin contact may cause slight or mild, transient irritation..

4. First Aid Measures

General advice	First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.
If inhaled	After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.
Eye Contact	For eye contact, flush with running water for at least 15 minutes.If eye irritation persists: get medical advice/attention.
Swallowed	After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.
Skin Contact	Immediately flush with plenty of water, while removing contaminated clothing.Immediately call a POISON CENTER or doctor/physician. Wash contaminated clothing before reuse.
Inhalation	If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Call a POISON CENTRE or doctor/physician if you feel unwell.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.Get medical attention if symptoms persist. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
Most important symptoms and effects, both acute and delaye	Harmful if swallowed or in contact with skin. Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis. May cause central nervous system effects. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.May cause respiratory irritation. Direct skin contact may cause slight or mild, transient irritation.
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

Flammability	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Flash Point	Dry powder Dry sand
Suitable extinguishing media	Water Foam Carbon dioxide (CO2) Dry powder
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Carbon oxides Hydrogen chloride gas Mixture with combustible ingredients. Vapors are heavier than air and may spread along floors. Forms explosive mixtures with air on intense heating. Development of hazardous combustion gases or vapours possible in the event of fire.
Further information	Remove container from danger zone and cool with water. Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Advice for firefighters	Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Oxides of phosphorus Sodium oxides Not combustible. Fire may cause evolution of: Oxides of phosphorus Ambient fire may liberate hazardous vapours.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.
Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Enviromental Precaution	Do not allow material to contaminate ground water system. If necessary, dike well ahead of the spill to prevent runoff into drains, sewers, or any natural waterway or drinking supply
Methods and materials for containment and cleaning	Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Use only non-sparking tools and equipment in the clean-up process. Avoid breathing mist or vapours. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13).Contact the proper local authorities. Refer to Section 13 for disposal of contaminated material.

7. Handling and Storage

Advice on protection against fire and explosion	Keep away from open flames, hot surfaces and sources of ignition.Take precautionary measures against static discharge.
Incompatible materials	Keep away from alkalis, strong oxidizing agents and metals. Provide containment walls of adequate capacity to hold any accidental spills.

Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Precautions for safe handling	Wear protective gloves and eye/face protection. Use only in well-ventilated areas. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep container tightly closed. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Keep away from flames and hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharges. Ground all equipment during handling.
Conditions for safe storage	Keep container tightly closed. Store in cool/well-ventilated place. Store locked up. Keep cool. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking. Empty containers may contain hazardous residues
Storage conditions	Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons. Light sensitive. Moisture sensitive.
Storage class	Storage class (TRGS 510): 6.1A: Combustible, acute toxic Cat. 1 and 2 / very toxic hazardous materials
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated
Advice on general occupational hygiene	Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.
Requirements for storage	Keep in cool and store under shade.

8. Exposure controls and personal protection

Exposure controls	Appropriate engineering controls Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Control parameters	Ingredients with workplace control parameters Contains no substances with occupational exposure limit values.
Engineering Control	Wear eye/face protection. Wear chemical goggles.
Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles
Body Protection	Protective clothing
Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Viton® Minimum layer thickness: 0,7 mm Break through time: 480 min Material tested:Vitoject® (KCL 890 / Aldrich Z677698, Size M) This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Chloroprene Minimum layer thickness: 0,65 mm Break through time: 30 min Material tested:KCL 720 Camapren®
Respiratory protection	Recommended Filter type: Respirator. The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Other Protection Measure	Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.
General hygiene considerations	Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical state	Clear liquid.
Colour	Colorless
Odour	Fruity odour.
Odor Threshold	No data available
pH	No data available
Melting Point	64°C
Boiling Point	192°C
Flash Point	74°C
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No data available
Explosive limits	No Data Available
Upper/lower flammability or explosive limits	0.5%/ 8.5%
Autoignition temperature	340°C
Decomposition temperature	No data available
Vapour pressure	0.3 mmHg
Density	1,1 g/cm3 at 25 °C - lit
Relative Density	0.942
Vapor density	(Air = 1) 5.5
Freezing point	No data available
Viscosity dynamic	1,380 mPa.s at 20 °C
Partition coefficient	1.51
Explosive properties	No data available
Solubility	Soluble(15g/L
Ignition temperature	No information available.
Particle characteristics	No data available

10. Stability and reactivity

Reactivity	Not normally reactive.
Stability	Stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur
Conditions to avoid	Open flames, sparks, high heat, direct sunlight, and close proximity to incompatible substances. Do not use in areas without adequate ventilation..
Incompatible materials	See Section 7 (Handling and Storage) for further details.
Hazardous decomposition products	None known, refer to hazardous combustion products in Section 5.

11. Toxicological information

Acute toxicity	Acute toxicity estimate Oral - 1.192,37 mg/kg (Calculation method) Acute toxicity estimate Oral - 560 mg/kg (Calculation method) LD50 Oral - Rat - male and female - 560 mg/kg (OECD Test Guideline 401) Symptoms: Possible damages:, Bloody vomiting Acute toxicity estimate Inhalation - 0,74 mg/l(Calculation method) Acute toxicity estimate Inhalation - 4 h - 4,98 mg/l - vapor(Calculation method) Acute toxicity estimate Inhalation - 4 h - 5 mg/l - vapor (Expert judgment) Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) Symptoms: Cough, Shortness of breath, mucosal irritations, Possible damages:, damage of respiratory tract, Lung edema, Symptoms may be delayed. Acute toxicity estimate Dermal - 124.400 mg/kg (Calculation method) Acute toxicity estimate Dermal - > 2.000 mg/kg (Calculation method)
Skin corrosion/irritation	Remarks: Causes skin irritation. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Serious eye damage/eye irritation	Remarks: Lacrimal irritation due to vapours. Remarks: Causes serious eye damage. Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Respiratory or skin sensitization	Local lymph node assay (LLNA) - Mouse Result: positive (OECD Test Guideline 429)
Toxic Effects on Human	May cause damage to the following organs: upper respiratory tract. Other Toxic Effects on Humans: Hazardous in case of skin contact (irritant, sensitizer), of ingestion, of inhalation (lung irritant, lung sensitizer).
Carcinogenicity	No data available
Germ cell mutagenicity	Local lymph node assay (LLNA) - Mouse Result: positive (OECD Test Guideline 429)
Reproductive toxicity	No data available
Specific target organ toxicity - single exposure	Inhalation - May cause respiratory irritation. - Respiratory system Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)
Special Remarks on other Toxi Effects on Humans	Acute Potential Health Effects: Skin: Causes skin irritation. May cause skin sensitization, an allergic reation, which becomes evident upon re-exposure to this material. Eyes: Causes eye irritation. Ingestion: Causes gastrointestinal (digestive) tract irritation with nausea, vomiting, and diarrhea. May be harmful if swallowed. Inhalation: Causes respiratory tract irritation. May cause chemical pneumonitis and pulmonary edema, inflammation, edema of bronchi and larynx. Chronic Potential Health Effects: Repeated or prolonged skin exposure may cause allergic reactions in sensitive individuals. Repeated or prolonged exposure by inhalation may affect respiration and metabolism.
Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher. RTECS: XS8925000 burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated. Systemic effects: Unconsciousness CNS disorders Damage to: Kidney Liver Other dangerous properties can not be excluded. This substance should be handled with particular care. Liver - Irregularities - Based on Human Evidence.

12. Ecological information

Bioaccumulative potential	No data available
Persistence and degradability	Biodegradability aerobic - Exposure time 14 d Result: 71 % - Readily biodegradable. (OECD Test Guideline 301C)

Toxicity to fish	Static test LC50 - Danio rerio (zebra fish) - 4 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	Static test EC50 - Daphnia magna (Water flea) - 6,1 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	Flow-through test NOEC - algae - 0,002 mg/l - 7 Days Remarks: (in analogy to similar products) (ECHA) The value is given in analogy to the following substances: sodium hypochlorite solution
Toxicity to bacteria	Static test EC50 - activated sludge - 563 mg/l - 3 h (OECD Test Guideline 209) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: sodium hypochlorite solution
Mobility in soil	No Information available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
Other adverse effects	Discharge into the environment must be avoided. Stability in water Test substance: Water Remarks: Rapid degradation.

13. Disposal considerations

Disposal methods	The material can be disposed of by removal to a licensed chemical destruction plant or by controlled incineration with flue gas scrubbing. Do not contaminate water, foodstuffs, feed or seed by storage or disposal. Do not discharge to sewer systems.
Contaminated packaging	Dispose of as unused product.
Waste treatment Method	See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

14. Transport information

UN number	ADR/RID: 1993 IMDG: 1993 IATA: 1993
UN proper shipping name	ADR/RID:Combustible liquid, n.o.s. (Ethylene glycol monobutyl ether acetate) IMDG:Combustible liquid, n.o.s. (Ethylene glycol monobutyl ether acetate) IATA:Combustible liquid, n.o.s. (Ethylene glycol monobutyl ether acetate)
Transport hazard class(es)	ADR/RID: IMDG: IATA:
Packaging group	ADR/RID: IMDG: IATA:
Environmental hazards	ADR/RID: NO IMDG: NO IATA: NO
Further information	No data available

15. Regulatory information

Inventory status	Components are on the following inventories: Polymaleic acid: - US TSCA, Canadian DSL, EU EINECS, Australian AICS, Korean, Philippine PICCS and Chinese Xi irritant R 36/38 Irritant to eyes & skin R 41 Risk of serious damage to eyes S24/25 Avoid contact with skin and eyes S26/28 In case of contact eyes & skin, rinse with plenty water and seek medical advice Section 312/313: Not listed. Not listed under California proposition 65.
Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
National legislation	Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. : ACUTE TOXIC
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.
Chemical Safety Assessment	For this product a chemical safety assessment was not carried out

16. Other information

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and weassume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.