



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

RXSOL-20-2045-210

Palm Fatty Acid Cleaner

Material Safety Data Sheet (MSDS)

1. Product and Company Identification

www.rxmarine.com

Product Name	RXSOL-19-1644-210
Product Type	Polyols 220Kg

Company Details:

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333 / 5555 / 9999
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Type of product:

Mixture polyether polyol No dangerous ingredients according to Regulation (EC) No. 1907/2006

3. Hazards Identification

www.rxmarine.com

Classification of the substance or mixture

GHS Classification: Not a dangerous substance according to GHS.

GHS-Labeling : Not a dangerous substance according to GHS.

4. First Aid Measures

www.rxmarine.com

Description of first aid measures

General advice:	Remove contaminated clothing.
-----------------	-------------------------------

If inhaled:	Take the person into the fresh air and keep him warm, let him rest; if there is difficulty in breathing, medical advice is required.
In case of skin contact:	In case of skin contact wash affected areas thoroughly with soap and plenty of water. Consult a doctor in the event of a skin reaction
In case of eye contact:	Hold the eyes open and rinse with preferably lukewarm water for a sufficiently long period of time (at least 10 minutes). Contact an ophthalmologist
If swallowed:	DO NOT induce the patient to vomit, medical advice is required

5. Fire-fighting Measures

www.rxmarine.com

Suitable extinguishing media:	Carbon dioxide (CO ₂), Foam, extinguishing powder, in cases of larger fires, water spray should be used.
Unsuitable extinguishing media:	High volume water jet
Special hazards arising from the substance or mixture:	Burning releases carbon monoxide, carbon dioxide, oxides of nitrogen and traces of hydrogen cyanide. In the event of fire and/or explosion do not breathe fumes
Advice for fire-fighters:	Firemen must wear self-contained breathing apparatus. Do not allow contaminated extinguishing water to enter the soil, ground-water or surface waters.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures:

Put on protective equipment (see section 8). Ensure adequate ventilation/exhaust extraction. Keep unauthorized

persons away.

Environment related measures:

Do not allow to escape into waterways, wastewater or soil.

Methods and material for containment and cleaning up:

Take up with absorbent for chemicals or, if necessary with dry sand and store in closed containers.

Reference to other sections:

For further disposal measures see section 13.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling:

When handling observe the usual precautionary measures for chemicals. Avoid contact with the skin and the eyes.

In all workplaces or parts of the plant where high concentrations of aerosols and/or vapors may be generated (e.g. during pressure release, mold venting or when cleaning mixing heads with an air blast), appropriately located exhaust ventilation must be provided in such a way that the WEL is not exceeded. The air should be drawn away from the personnel handling the product. The efficiency of the exhaust equipment should be periodically checked.

Precautions should generally be taken against electrostatic charges according to the equipment used and the way the product is handled and packaged.

Keep away from foodstuffs, drinks and tobacco. Wash hands before breaks and at the end of workday. Keep working clothes separately. Change contaminated or soaked clothing.

Conditions for safe storage, including any incompatibilities: Keep container tightly closed and dry.

Storage temperature regarding personal safety: max. 50 °C.

Further specific information see our : "Technical Information"

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters :

No information on Exposure Limit Values necessary according to EC directive 2006/121/EG. For technical protective measures to limit exposure see also Chapter 7 "Handling and storage".

Exposure controls

Respiratory protection:

Unless the product is entirely enclosed, do not handle it until you have studied the respiratory precautions issued by the appropriate authority or accident prevention association. At substantial vapor concentrations respirators must be used. Put on full-mask respirator with filter type ABEK.

Hand protection:

Protective gloves are recommended. Conditionally suitable materials for protective gloves; EN 374: Nitrile rubber - NBR (≥ 0.35 mm) Breakthrough time not tested; dispose of immediately after contamination.

Eye protection:

Wear eye/face protection.

Skin and body protection:

Wear suitable protective clothing.

Safety precautions for handling freshly molded polyurethane parts: see section 16

9. Physical and chemical properties

www.rxmarine.com

Appearance:	viscous
Colour:	colourless
Odour:	slight inherent odour
Odour Threshold:	not established
pH:	ca. 6,5
Pour point	ca. -36 °C
Initial boiling point:	> 200 °C
Flash point:	ca. 235 °C
Evaporation rate:	not established
Flammability (solid, gas):	not applicable
Burning number:	not applicable
Vapour pressure:	0,00133 hPa at 25 °C
Vapour density:	not established
Density:	1,02 g/cm ³ at 20 °C
Water solubility:	slightly soluble
Surface tension:	not established
Partition coefficient(n-octanol/water):	not established
Autoignition temperature:	not applicable
Ignition temperature:	not established
Decomposition temperature:	not established
Viscosity, dynamic:	788 mPa.s at 20 °C 575 mPa.s at 25 °C 50 mPa.s at 95 °C
Explosive properties:	not established
Dust explosion class:	not applicable
Oxidising properties:	not established

10. Stability and reactivity

www.rxmarine.com

Chemical stability: No decomposition below initial boiling point.

Possibility of hazardous reactions: No hazardous reactions when used as directed.

Hazardous decomposition products: No hazardous decomposition products when stored and handled correctly.

11. Toxicological information

www.rxmarine.com

Toxicological studies on the product are not yet available.

An expected acute oral toxicity as LD50 in rats will be in the order of >2000 mg/kg as derived from products with similar composition.

Irritant/caustic action in analogy to a comparable product.

Skin effect: No skin irritation is expected.

Eye effect: Weak irritation of the eyes possible

12. Ecological information

www.rxmarine.com

Ecotoxicological studies of the product are not available.

Do not allow to escape into waterways, wastewater or soil.

13. Disposal considerations

www.rxmarine.com

Dispose in accordance with applicable international, national and local laws, ordinances and statutes. For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

Waste treatment methods :

After containers have been emptied as thoroughly as possible (e.g. by pouring, scraping or draining until "drip-dry"), they can be sent to an appropriate collection point set up within the framework of the existing take-back scheme of the chemical industry. Containers must be recycled in compliance with national legislation and environmental regulations.

None disposal into waste water.

14. Transport information

www.rxmarine.com

ADR/RID :Not dangerous goods

ADN : Not dangerous goods

ADNR : (tanker only) Not dangerous goods

IATA : Not dangerous goods

IMDG : Not dangerous goods

Special precautions for user : Not dangerous cargo.Keep away from foodstuffs, acids and alkalis.

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Product name: Glycerol propoxylated/ethoxylated, Pollution category: Z - Ship type: 3

15. Regulatory information

www.rxmarine.com

Information Not Fund

16. Other information

www.rxmarine.com

Safety precautions for handling freshly molded polyurethane parts:

Depending on the production parameters, any uncovered surfaces of polyurethane moldings produced using this raw material may contain traces of substances (e. g. starting and reaction products, catalysts, release agents) with hazardous characteristics. Skin contact with traces of these substances must be avoided. When demolding or otherwise handling freshly molded polyurethane parts, protective textile gloves must be worn as a minimum. Their palm and finger areas should preferably be coated on the outside with nitrilerubber, PVC or polyurethane. Protective gloves should be changed daily. The wearing of protective clothing suited to the conditions normally encountered when handling freshly molded polyurethane parts is recommended.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Further information:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.