



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

RXSOL-33-3356-050

Phosphonic Acid Solution

Material Safety Data Sheet (MSDS)

www.rxmarine.com

1. Product and Company Identification

Product Name	Phosphonic Acid Solution
Part Number	RXSOL-33-3356-050

Company Details:....

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA

Branch : Kandla, Mumbai , Chennai, Vizag, Kolkata, UAE , OMAN , CANADA and KENYA

Phone	+91 22 20871200 - 1400
Fax	+91 22 27612100 ::::AOH :0091 9821214367
Email	mail@rxmarine.com
Website	www.rxmarine.com

www.rxmarine.com

2. Composition / Information on ingredients

Substances

Synonyms	Phosphonic acid
Formula	H3O3P
Molecular weight	82,00 g/mol
CAS-No.	13598-36-2
EC-No.	237-066-7
Index-No.	015-157-00-0

Component	Classification	Concentration
Phosphorous acid		
CAS-No. 13598-36-2 EC-No 237-066-7 Index-No. 015-157-00-0	Met. Corr. 1; Acute Tox. 4; Skin Corr. 1A; Eye Dam. 1; H290, H302, H314, H318	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

3. Hazards Identification

www.rxmarine.com

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008	Corrosive to Metals (Category 1), H290 Acute toxicity, Oral (Category 4), H302 Skin corrosion (Sub-category 1A), H314 Serious eye damage (Category 1), H318 For the full text of the H-Statements mentioned in this Section, see Section 16.
--	--

Label elements

Signal Word	Danger
Hazard Statements	H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage.
Precautionary Statements	P260 Do not breathe dusts or mists. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth. P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
Supplemental Hazard Statements	None
Other hazards	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

4. First Aid Measures

www.rxmarine.com

Description of first aid measures

General advice	First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.
If inhaled	After inhalation: fresh air. Call in physician.
In case of skin contact	In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.
In case of eye contact	After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.
If swallowed	After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.
Most important symptoms and effects, both acute and delayed	The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11
Indication of any immediate medical attention and special treatment needed	No data available

5. Fire-fighting Measures

www.rxmarine.com

Extinguishing media

Suitable extinguishing media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	For this substance/mixture no limitations of extinguishing agents are given. For this substance/mixture no limitations of extinguishing agents are given.
Special hazards arising from the substance or mixture	Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Oxides of phosphorus Not combustible. Ambient fire may liberate hazardous vapours.
Advice for firefighters	Wear self-contained breathing apparatus for firefighting if necessary. Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.
Further information	Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system. spray to keep fire-exposed containers cool. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures	Advice for non-emergency personnel: Avoid inhalation of dusts. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.
Environmental precautions	Do not let product enter drains.
Methods and materials for containment and cleaning up	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up affected area. Avoid generation of dusts.
Reference to other sections	For disposal see section 13.

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

Advice on safe handling	Work under hood. Do not inhale substance/mixture.
Hygiene measures	Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.
Conditions for safe storage, including any incompatibilities Storage conditions	Tightly closed. Dry.
Storage class	Storage class (TRGS 510): 8A: Combustible, corrosive hazardous materials
Specific end use(s)	Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters

Ingredients with workplace control parameters

Exposure controls

Personal protective equipment

Eye/face protection	Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles
---------------------	--

Skin protection	This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Full contact Material: Chloroprene Minimum layer thickness: 0,65 mm Break through time: 480 min Material tested:KCL 720 Camapren® This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de). Splash contact Material: Latex gloves Minimum layer thickness: 0,6 mm Break through time: 60 min Material tested:Lapren® (KCL 706 / Aldrich Z677558, Size M).
Body Protection	Flame retardant antistatic protective clothing.
Respiratory protection	Recommended Filter type: Filter A-(P3) The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.
Control of environmental exposure	Do not let product enter drains.

9. Physical and chemical properties

www.rxmarine.com

Physical state	Flakes
Colour	White
Odor	Odorless
Melting point/freezing point	Melting point/range: 63 - 74 °C at 1.013 hPa - OECD Test Guideline 102
Initial boiling point and boiling range	259 °C at 1.013 hPa - OECD Test Guideline 103
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	No data available
Flash point	Not applicable
Autoignition temperature	Not auto-flammable
Decomposition temperature	No data available
pH	At 20 °C acidic materials.Extremely flammable in the presence of the following materials or conditions: oxidizing materials.
Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: No data available
Water solubility	Soluble

Partition coefficient: n-octanol/water	- Not applicable for inorganic substances
Vapor pressure	< 0,1 hPa at 20 °C - OECD Test Guideline 104
Density	1,651 g/cm ³ at 25 °C - lit.
Relative density	No data available
Relative vapor density	No data available
Particle characteristics	No data available
Explosive properties	No data available
Oxidizing properties	The product has been shown not to be oxidizing in a test following Directive 67/548/EEC (Method A17, oxidizing properties).
Other safety information	No data available

10. Stability and reactivity

www.rxmarine.com

Reactivity	No data available
Chemical stability	The product is chemically stable under standard ambient conditions (room temperature) .
Possibility of hazardous reactions	No data available
Conditions to avoid	No information available
Incompatible materials	Strong oxidizing agents
Hazardous decomposition products	In the event of fire: see section 5

11. Toxicological information

www.rxmarine.com

Information on toxicological effects

Acute toxicity	LD50 Oral - Rat - male and female - 1.560 - 1.580 mg/kg (OECD Test Guideline 401) Inhalation: No data available
Skin corrosion/irritation	Skin - Rabbit Result: Causes burns. Remarks: (ECHA)
sensitization	Not available
mutagenicity	Not available
Carcinogenicity	Not available
Reproductive toxicity	Not available
Teratogenicity	Not available
Specific target organ toxicity (single exposure)	Not available.
Specific target organ toxicity (repeated exposure)	Not available.
Aspiration hazard	Not available.
Information on the likely routes of exposure	Not available.

12. Ecological information

www.rxmarine.com

Persistence and degradability	No data available
Toxicity to fish	Static test LC50 - Oncorhynchus mykiss (rainbow trout) - 75 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	Static test EC50 - Daphnia magna (Water flea) - 42,81 mg/l - 48 h (OECD Test Guideline 202) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: maleic acid
Toxicity	Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 1.520 mg/l - 96 h
Toxicity to bacteria	EC10 - Bacteria - 14 mg/l - 72 h Remarks: (Lit.) EC5 - E.coli - 15.000 mg/l Remarks: (Lit.) (maximum permissible toxic concentration)
Toxicity to algae	Static test ErC50 - Pseudokirchneriella subcapitata (green algae) - 74,35 mg/l - 72 h (OECD Test Guideline 201) Remarks: (in analogy to similar products) The value is given in analogy to the following substances: maleic acid
Products Biodegradation	The methods for determining the biological degradability are not applicable to inorganic substances.
Mobility in soil	No data available
Results of PBT and vPvB assessment	This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Endocrine disrupting properties	No data available
Other adverse effects	No data available .

13. Disposal considerations

www.rxmarine.com

Product	Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.
Contaminated packaging	Dispose of as unused product.
Waste treatment Method	See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

14. Transport information

www.rxmarine.com

UN number	ADR/RID:2834	IMDG:2834	IATA: 2834
UN proper shipping name	ADR/RID: PHOSPHOROUS ACID IMDG: PHOSPHOROUS ACID IATA: Phosphorous acid		
Transport hazard class(es)	ADR/RID: 8	IMDG: 8	IATA:8
Packaging group	ADR/RID: III	IMDG: III	IATA:III
Environmental hazards	ADR/RID: No	IMDG: No	IATA: No
Special precautions for user	No data available		

Further information	Not classified as dangerous in the meaning of transport regulations.
---------------------	--

15. Regulatory information

www.rxmarine.com

Safety, health and environmental regulations/legislation specific for the substance or mixture	This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.
Other regulations	Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable. Take note of Dir 94/33/EC on the protection of young people at work.
Chemical Safety Assessment	For this product a chemical safety assessment was not carried out

16. Other information

www.rxmarine.com

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall we be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages.
-------------------	--

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit varanasichemical.com. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.