



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

Material Safety Data Sheet (MSDS)

RXSOL-41-8341-025

Odor Neutralizer Membrane Smoke Odor Solution Fragrance

1. Product and Company Identification

www.rxmarine.com

Product Name	Reverse Demulsifier
Part Number	RXSOL-20-8183-210

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Branch : Mumbai, Kandla, Vizag, Chennai, Kolkat, UAE, Oman, Canada

Phone	+91 22 20871200 / 300 / 400
Fax	+91 22 2781 1318 ::::AOH :0091 9821214367
Email	123@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Name of Substance	%w/w	Cas No
Light Aromatic Naphtha	20-30	64742-95-6
1,2,4-Trimethylbenzene	20-30	95-63-6
Alkylaryl sulfonates	10-20	68425-60-5
Alkylaryl sulfonates	10-20	68425-61-6
1,3,5- Trimethylbenzene	5-10	108-67-8
2-Ethylhexanol	5-10	104-76-7
Xylene	1-5	1330-20-7
1,2,3-Trimethylbenzene	1-5	526-73-8
Cumene	0.1-1	98-82-8
Ethylbenzene	0.1-1	100-41-4
Propargyl alcohol	1-5	107-19-7
Aluminum chloride	1-5	11330-20-7

Proprietary Blend	10-20	
-------------------	-------	--

3. Hazards Identification

www.rxmarine.com

Signal Word	Warning
Hazard Statements	May be corrosive to metals. Causes severe skin burns and eye damage. Causes damage to organs through prolonged or repeated exposure if inhaled. (lungs). May cause damage to organs through prolonged or repeated exposure if swallowed.
Precautionary statements - prevention	Wear protective gloves: > 8 hours (breakthrough time): Nitrile or Neoprene gloves.. Wear eye or face protection. Wear protective clothing. Keep only in original container. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling
Precautionary statements - response	Absorb spillage to prevent material damage. Get medical attention if you feel unwell. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
Disposal	Store locked up. Store in corrosive resistant container with a resistant inner liner.

4. First Aid Measures

www.rxmarine.com

Skin Contact	Get medical attention immediately. Call a poison center or physician. Wash affected area with soap and mild detergent for at least 20 - 60 minutes. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye Contact	Get medical attention immediately. Call a poison center or physician. Immediately flush the eye(s) continuously with lukewarm, gently flowing water for at least 20-60 minutes while holding the eyelid(s) open. Check for and remove any contact lenses. Chemical burns must be treated promptly by a physician.

Inhalation:	Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection for first Aider	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to Physician	In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

5. Fire-fighting Measures

www.rxmarine.com

Extinguishing media

Suitable extinguishing media	Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	carbon dioxide, carbon monoxide, nitrogen oxides, halogenated compounds, metal oxide/ oxides
Special protective actions for fire-fighters	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Further Information	Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

6. Accidental Release Measures

www.rxmarine.com

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders :	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".
Environmental Precaution	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for containment and cleaning	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment

7. Handling and Storage

www.rxmarine.com

Precautions for safe handling

Protective measures	Wear personal protective equipment. Do not get Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage. prevent material damage. product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage. from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage.
Advice on general occupational hygiene. occupational hygiene.	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in corrosive resistant container with a resistant inner liner. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls and personal protection

www.rxmarine.com

Control parameters

Occupational exposure limits

Engineering Control	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.
Personal Protection	Eye/face Protection : Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Skin and body protection : Wear appropriate protective gloves and clothing to prevent skin exposure. Long sleeved clothing.Flame retardant antistatic protective clothing. Respiratory Protection : Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.
Hygiene Measures	Handle in accordance with good industrial hygiene and safety practice.
Exposure Limits	TWA: 100 (ppm) [Canada] TWA: 435 (mg/m3) [Canada] TWA: 434 STEL: 651 (mg/m3) from ACGIH (TLV) [United States] TWA: 100 STEL: 150 (ppm) from ACGIH (TLV) [United States] Consult local authorities for acceptable exposure limits.



Gloves



Suit

9. Physical and chemical properties

www.rxmarine.com

Appearance

Physical state	Liquid
Colour	Colourless
Odor	Pungent.
Odor Threshold	Not Available
pH	2.6
Melting Point	Not available
Boiling Point	Not available
Flash Point	Closed cup: >93.4°C (>200.1°F) [SFCC]
Evaporation Rate	Not available
Flammability (solid, gas)	Slightly flammable in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. sparks and static discharge and heat.
Lower and upper Explosive limits	Not available

Vapour pressure	6.1 kPa (45.7 mm Hg) @ 22°C 6.1 kPa (45.7 mm Hg) @ 22°C . 6.1 kPa (45.7 mm Hg) @ 22°C . 6.1 kPa (45.7 mm Hg) @ 22°C .
Vapour Density	>1 [Air = 1]
Relative density	1.259 (15.6°C)
Density	10.49 (lbs/gal)
Solubility in water	Soluble
Partition coefficient: noctanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Dynamic (25°C): 47.4 cP
Pour Poin	-40°C (-40°F)

10. Stability and reactivity

www.rxmarine.com

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	No specific data.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials and metals
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO2),
Hazardous Polymerization	Hazardous polymerization does not occur. Hazardous Reactions None under normal processing

11. Toxicological information

www.rxmarine.com

Acute oral toxicity	Symptoms: Gastrointestinal disturbance, Risk of aspiration upon vomiting., Pulmonary failure possible after aspiration of vomit.
Acute dermal toxic	Acute toxicity estimate : 1,134 mg/kg
Skin corrosion	Drying-out effect resulting in rough and chapped skin. Mixture causes skin irritation.
Toxic Effects on Humans	Acute Potential Health Effects: Skin: Causes skin irritation. Can be absorbed through skin. Eyes: Causes eye irritation. Inhalation: Vapor causes respiratory tract and mucous membrane irritation.
Special Remarks on Chronic Effects on Humans	Detected in maternal milk in human. Passes through the placental barrier in animal. Embryotoxic and/or foetotoxic in animal. May cause adverse reproductive effects (male and femael fertility (spontaneous abortion and fetotoxicity) and birth defects based animal data.

Further information After absorption:	Headache, somnolence, Dizziness, euphoria, agitation, spasms, narcosis Effect potentiated by: ethanol Damage to: Kidney, Central nervous system, Liver
--	---

12. Ecological information

www.rxmarine.com

Toxicity to Fish	No information available.
COD and BOD 5	Not Available
Products of Biodegradation:	No information available.
Mobility in soil	No information available.
Results of PBT and vPvB assessment	Substance(s) in the mixture do(es) not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII, or a PBT/vPvB assessment was not conducted.
Other adverse effects	Additional ecological information Discharge into the environment must be avoided.

13. Disposal considerations

www.rxmarine.com

Waste treatment Method	Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself
---------------------------	---

14. Transport information

www.rxmarine.com

DOT

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

TDG

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

IATA

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

IMDG/IMO

UN Number	UN1307
Proper shipping name	XYLENE
Hazard Class	3
Packing group	III

15. Regulatory information

www.rxmarine.com

Federal and State Regulation	Connecticut hazardous material survey.: Xylenes Illinois chemical safety act: Xylenes New York acutely hazardous substances: Xylenes Rhode Island RTK hazardous substances: Xylenes Pennsylvania RTK: Xylenes Minnesota: Xylenes Michigan critical material: Xylenes Massachusetts RTK: Xylenes Massachusetts spill list: Xylenes New Jersey: Xylenes New Jersey spill list: Xylenes Louisiana spill reporting: Xylenes California Director's List of Hazardous Substances: Xylenes TSCA 8(b) inventory: Xylenes SARA 302/304/311/312 hazardous chemicals: Xylenes SARA 313 toxic chemical notification and release reporting: Xylenes CERCLA: Hazardous substances.: Xylenes: 100 lbs. (45.36 kg)
Other Regulation	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200). EINECS: This product is on the European Inventory of Existing Commercial Chemical Substances.
WHMIS (Canada)	CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2A: Material causing other toxic effects (VERY TOXIC).
DSCL (EEC)	R11- Highly flammable. R38- Irritating to skin. R41- Risk of serious damage to eyes.

HMIS	
Health Hazard	: 3
Fire Hazard	: 3
Reactivity	: 0
Personal Protection	: H

Fire :	
Health Hazard	: 3
Fire Hazard	: 3
Reactivity	: 0
Specific Hazard	: ..

16. Other information

www.rxmarine.com

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	---

11330-20-7

11330-20-7

11330-20-7

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.