



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

RXSOL-41-8665-025

DYE-LOC CR14

Material Safety Data Sheet (MSDS)

1. Product and Company Identification

www.rxmarine.com

Product Name	Ammonium Persulfate Pwd
Part Number	RXSOL-60-6216-025

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Stock Point : Mumbai, Kandla, Chennai, Visakhapatnam, Kolkata, Fujairah, Muscat, Canada

Phone	+91 22 65113333 / 5555 / 9999
Fax	+91 22 2781 1318 ::AOH :0091 9821214367
Email	123@rxmarine.com
Website	www.rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Name of Substance	Cas Number	EC Number	Wight %
Ammonium Persulfate	7727-54-0	231-786-5	100%

3. Hazards Identification

www.rxmarine.com

Signal Word	Danger
Hazard Statements	H272 May intensify fire; oxidizer. H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.
Precautionary statements - prevention	P280 Wear protective gloves.

Precautionary statements - response	P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/ physician
-------------------------------------	--

4. First Aid Measures

www.rxmarine.com

Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Cold water may be used. Get medical attention.
Skin Contact	In case of contact, immediately flushes skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Cover the irritated skin with an emollient. Cold water may be used. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if symptoms occur.
Ingestion:	Do not induce vomiting. Obtain medical attention. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration.
Notes to Physician	Treat symptomatically

5. Fire-fighting Measures

www.rxmarine.com

Flammability	May be combustible at high temperature.
Flash Point	CLOSED CUP: Higher than 93.3°C (200°F).
Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Hazardous combustion products	Fire may cause the evolution of Sulphur oxides, nitrogen oxides.
Protective Equipment	Use personal protective equipment.
Specific Hazards Arising from the Chemical	Has a fire-promoting effect due to the release of oxygen. Ambient fire may liberate hazardous vapours.

6. Accidental Release Measures

www.rxmarine.com

Spillage	Oxidizing material. Stop leak if without risk. Avoid contact with a combustible material (wood, paper, oil, clothing...). Keep substance damp using water spray. Do not touch spilled material. Prevent entry into sewers, basements or confined areas dike if needed. Eliminate all ignition sources. Call for assistance on disposal.
Personal Protection	Advice for non-emergency personnel: Avoid inhalation of dust. Evacuate the danger area, observe emergency procedures, consult an expert. Advice for emergency responders: Protective equipment see section 8.
Environmental Precaution	Do not let product enter drains.

Methods and materials for containment and cleaning	Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up dry. Dispose of properly. Clean up the affected area. Avoid generation of dust
--	--

7. Handling and Storage

www.rxmarine.com

Handling	Keep away from heat. Keep away from sources of ignition. Keep away from combustible material.. Empty containers pose a fire risk, evaporate the residue under a fume hood. Ground all equipment containing material. Do not ingest. Do not breathe dust. Wear suitable protective clothing. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. Keep away from incompatibles such as reducing agents, combustible materials, organic materials, metals
Storage	Strong Oxidizer. Moisture Sensitive. Keep container tightly closed. Keep container in a cool, well-ventilated area. Separate from acids, alkalies, reducing agents and combustibles. See NFPA 43A, Code for the Storage of Liquid and Solid Oxidizers. Do not store above 23°C (73.4°F).
Advice on general occupational hygiene	Advice on safe handling Observe label precautions. Change contaminated clothing. Wash hands after working with substance.

8. Exposure controls and personal protection

www.rxmarine.com

Engineering Control	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.
Personal Protection	Eye/face Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166. Skin and body protection: Wear appropriate protective gloves and clothing to prevent skin exposure. Respiratory Protection : Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator exposure limits are exceeded or if irritation or other symptoms are experienced.
Other Protection Measure	Handle in accordance with good industrial hygiene and safety practice.
Exposure Limit	Not Available



Gloves



Suit

9. Physical and chemical properties

www.rxmarine.com

Form	Solid
Colour	White

Odour	Odourless
Odor Threshold	Not Applicable
pH	3.2 - 3.5 at 100 g/l 20 °C
Melting Point	120 °C (decomposition)
Boiling Point	Not Applicable
Flash Point	Not Applicable
Evaporation Rate	Not Applicable
Flammability (solid, gas)	No Data Available
Explosive limits	No Data Available
Vapour pressure	No Data Available
Vapour Density	No Data Available
Specific Gravity	1.98 g/cm ³ at 20 °C
Partition coefficient	No data available
Explosive properties	None
Solubility	Soluble in water 620 g/l at 20 °C
Ignition temperature	No information available.

10. Stability and reactivity

www.rxmarine.com

Reactivity	Forms explosive mixtures with air on intense heating.
Stability	Product is stable.
Possibility of hazardous reactions	Violent reactions possible with: Amines, Strong oxidizing agents Violent polymerisation may be caused by: Strong bases, Strong acids
Conditions to avoid	Strong Heating
Incompatible materials	Aluminium, various metals, Mild steel
Hazardous Polymerization	Hazardous polymerization does not occur.

11. Toxicological information

www.rxmarine.com

Rout Of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
Toxicity to Animal	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 100 mg/kg [Mouse]. Acute dermal toxicity (LD50): >2500 mg/kg [Rat]. Acute toxicity of the vapor (LC50): 480 mg/m 4 hours [Rat]. 3

Toxic Effects on Humans	CARCINOGENIC EFFECTS: Classified A4 (Not classifiable for human or animal.) by ACGIH [Glutaraldehyde]. MUTAGENIC EFFECTS: Mutagenic for mammalian somatic cells. [Glutaraldehyde]. Mutagenic for bacteria and/or yeast. [Glutaraldehyde]. DEVELOPMENTAL TOXICITY: Classified Reproductive system/toxin/female, Reproductive system/toxin/male [SUSPECTED] [Glutaraldehyde]. Contains material which may cause damage to the following organs: blood, the reproductive system, liver, mucous membranes, spleen, central nervous system (CNS), Urinary system.
Special Remarks on other Toxic Effects on Humans:	Potential Health Effects: Eye: Causes severe eye irritation. May cause eye injury or chemical conjunctivitis. Skin: Causes moderate to severe skin irritation. It may be absorbed through the skin, although poorly. May cause allergic contact dermatitis with itching and skin rash. May cause staining of the skin and nails to a brown or golden brown color. Ingestion: Harmful if swallowed. May cause severe irritation of the digestive tract with burning sensation in the chest, abdominal pain, cramping, vomiting, diarrhoea (perhaps bloody diarrhoea), vascular collapse, and coma. May also affect liver (increased liver enzymes, liver damage), spleen, blood (normocytic anemia), metabolism (weight loss), behavior (somnolence, excitement, dizziness, lethargy, ataxia, seizures), metabolism (weight loss), urinary system (abnormal renal function, anuria) Inhalation: Harmful if inhaled. Can cause respiratory tract irritation and sudden headaches.

12. Ecological information

www.rxmarine.com

Eco Toxicity	Not Available
COD and BOD 5	Not Available
Products of Biodegradation:	No Information available
Mobility in soil	No Information available
Results of PBT and vPvB assessment	Substance(s) in the mixture do(es) not meet the criteria for PBT or vPvB according to Regulation (EC) No 1907/2006, Annex XIII, or a PBT/vPvB assessment was not conducted..
Other adverse effects	Discharge into the environment must be avoided.

13. Disposal considerations

www.rxmarine.com

Waste treatment Method	Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself
------------------------	---

14. Transport information

www.rxmarine.com

DOT

UN Number	UN1444
Proper shipping name	AMMONIUM PERSULPHATE
Hazard Class	5.1
Packing group	III

TDG

UN Number	UN1444
Proper shipping name	AMMONIUM PERSULPHATE
Hazard Class	5.1
Packing group	III

IATA

UN Number	UN1444
Proper shipping name	AMMONIUM PERSULPHATE
Hazard Class	5.1
Packing group	III

IMDG/IMO

UN Number	UN1444
Proper shipping name	AMMONIUM PERSULPHATE
Hazard Class	5.1
Packing group	III

15. Regulatory information

www.rxmarine.com

16. Other information

www.rxmarine.com

Other Information	The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if Rx Marine International has been advised of the possibility of such damages. DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.
-------------------	---

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.