



# RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

## Material Safety Data Sheet (MSDS)

**RXSOL-41-8882-025**

GROUT DOCTOR NEUTRAL CLEANER

### 1. Product and Company Identification

[www.rxmarine.com](http://www.rxmarine.com)

|              |                                                              |
|--------------|--------------------------------------------------------------|
| Product Name | Battery Fluid Alkali                                         |
| Product Type | RXSOL-15-1103-025 Batteries Liquid (Electrolyte) for vehicle |

Battery fluid, alkali (Liquid Electrolyte (Potassium Hydroxide + Lithium Hydroxide + Proprietary blend with Water))

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

STOCK Point :

|       |                                                          |
|-------|----------------------------------------------------------|
| Phone | +91 22 27815540 / 41 / 42                                |
| Fax   | +91 22 2781 1318 ::::AOH :0091 9322594669                |
| Email | <a href="mailto:mail@rxmarine.com">mail@rxmarine.com</a> |

STOCK POINT : Kandla - Gandhidham, Mumbai, Chennai - Ennore, Visakhapatnam, Kolkata, Fujairah,

### 2. Composition / Information on ingredients

[www.rxmarine.com](http://www.rxmarine.com)

|                 |                               |           |         |                         |
|-----------------|-------------------------------|-----------|---------|-------------------------|
| Ingredients     | Proprietary blended D.I.Water | 7732-18-5 | 76-78%  | To complete solution    |
| Main Ingrident  | Potassium hydroxide(KOH)      | 1310-58-3 | 20-30%  | 230 to 250 Gram Per Ltr |
| Other Ingrident | Lithium Hydroxide             | 1310-65-2 | 2 - 5 % | 20 to 25 Gram per Ltr   |

### 3. Hazards Identification

[www.rxmarine.com](http://www.rxmarine.com)

|            |                                                                                                                                                                                                                                                                                                                                                                                            |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation | Mists and vapours are corrosive and can cause sever irritation and damage to mouth, nose, lungs, and throat. Exposure symptoms are from coughing, sneezing, tickling sensations in nose and throat to larngelaedma, bronchitis,and pulmonary edema. Prolonged exposure can result in erosion and discoloration of teeth, chronic irritation of the nose eyes throat and respiratory tract. |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                           |                                                                                                                                                                                                                                                 |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Skin Contact / Absorption | Severe irritation and burns to all human tissue. Repeated skin contact may cause dermatitis.                                                                                                                                                    |
| Eye Contact               | Contact with even small amounts can result in severe damage (corneal burns and/or necrosis and conjunctivitis) which may result in sight loss. Dilute solution of sulphuric acid may produce temporary effects from which recovery is possible. |
| Ingestion                 | Severe irritation or burning of the mouth, throat, and stomach walls. May be fatal. Prolonged exposure can result in erosion and discoloration of teeth, chronic irritation of the nose eyes throat and respiratory tract.                      |
| Exposure Limits           | ACGIH: 1mg/m <sup>3</sup> ; 3mg/m <sup>3</sup><br>NIOSH: TWA = 1mg/m <sup>3</sup> ; IDLH = 15mg/m <sup>3</sup><br>OSHA: TWA = 1mg/m <sup>3</sup>                                                                                                |

#### 4. First Aid Measures

[www.rxmarine.com](http://www.rxmarine.com)

|                           |                                                                                                                                                                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation                | Remove victim to fresh air. Give artificial respiration only if breathing has stopped. If breathing is difficult, give oxygen. Seek immediate medical attention.                                                                             |
| Skin Contact / Absorption | Remove contaminated clothing. Wash affected area with soap and water. Seek medical attention if irritation occurs or persists                                                                                                                |
| Eye Contact               | Flush immediately with water for at least 15 minutes. Forcibly hold eyelids apart to ensure complete irrigation of eye tissue. Seek immediate medical attention                                                                              |
| Ingestion                 | Do not induce vomiting. If vomiting occurs, lean victim forward to prevent breathing in vomitus. Give large amounts of water. Do not give anything by mouth to an unconscious or convulsing person. Seek immediate medical attention.        |
| Additional Information    | Medical conditions that may be aggravated by exposure include asthma, bronchitis, emphysema, and other lung diseases, chronic nose, sinus or throat conditions. In the event of skin, eye contact, rapid and thorough flushing is essential. |

#### 5. Fire-fighting Measures

[www.rxmarine.com](http://www.rxmarine.com)

|                                  |                                                                                                                                                          |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Conditions of Flammability:      | Non-flammable                                                                                                                                            |
| Means of Extinction:             | Product does not burn. Suitable: Class D-Dry chemical, Carbon dioxide (CO <sub>2</sub> ) , Carbon dioxide blanket, Sand, foam.                           |
| Flash Point:                     | Not applicable.                                                                                                                                          |
| Auto-ignition Temperature:       | Not applicable                                                                                                                                           |
| Upper Flammable Limit            | Not applicable                                                                                                                                           |
| Lower Flammable Limit            | Not applicable                                                                                                                                           |
| Hazardous Combustible Products   | Solution process causes formation of corrosive mists.                                                                                                    |
| Special Fire Fighting Procedures | Wear NIOSH-approved self-contained breathing apparatus and protective clothing.                                                                          |
| Explosion Hazards                | Evolution of explosive hydrogen gas on contact with most metals. May ignite combustible material. Not sensitive to mechanical impact or static discharge |

#### 6. Accidental Release Measures

[www.rxmarine.com](http://www.rxmarine.com)

|                        |                                                                                                                                              |
|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Leak /Spill            | Wear appropriate personal protective equipment. Ventilate area. Stop or reduce leak if safe to do so. Prevent material from entering sewers. |
| Deactivating Materials | Lime, limestone, sodium carbonate (soda ash), sodium bicarbonate, dilute sodium hydroxide.                                                   |

## 7. Handling and Storage

[www.rxmarine.com](http://www.rxmarine.com)

|                      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Handling Procedures  | Use proper equipment for lifting and transporting all containers. Use sensible industrial hygiene and housekeeping practices. Wash thoroughly after handling. Avoid all situations that could lead to harmful exposure. Ventilate area of leak or spill. Keep unnecessary and unprotected people away from area of spill. Wear appropriate personal protective equipment as specified in Section 8. Spills: Pick up and place in a suitable container for reclamation or disposal, using a method that does not generate dust. Do not flush caustic residues to the sewer. Residues from spills can be diluted with water, neutralized with dilute acid such as acetic, hydrochloric or sulfuric. Absorb neutralized caustic residue on clay. |
| Storage Requirements | Store in a cool, dry, well-ventilated place. Keep container tightly closed and away from incompatible materials. Keep in a tightly closed container, stored in a cool, dry, ventilated area. Protect against direct sunlight and physical damage. Isolate from incompatible substances. Avoid direct sunlight, high temperature and high humidity. Store in a cool and dry place. (Between 10 to 30 degree C & humidity of 45 to 85 % ). Do not mix OR use like stirrer used for lead acid batteries for mixing the electrolyte as this will neutralize the alkaline electrolyte.                                                                                                                                                             |

## 8. Exposure controls and personal protection

[www.rxmarine.com](http://www.rxmarine.com)

|                          |                                                                                                                                                                                                                           |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Protective Equipment     |                                                                                                                                                                                                                           |
| Eyes                     | Chemical goggles, full-face shield, or a full-face respirator is to be worn at all times when product is handled. Contact lenses should not be worn; they may contribute to severe eye injury.                            |
| Respiratory              | Use NIOSH-approved respirator-full facepiece with cartridges (acid-gas and mists) or self-contained breathing apparatus.                                                                                                  |
| Gloves                   | Impervious gloves of chemically resistant material (rubber or PVC) should be worn at all times. Wash contaminated clothing and dry thoroughly before reuse.                                                               |
| Clothing                 | Body suits, aprons, and/or coveralls of chemical resistant material should be worn at all times. Wash contaminated clothing and dry thoroughly before reuse.                                                              |
| Footwear                 | Impervious boots of chemically resistant material should be worn at all times.                                                                                                                                            |
| Engineering Controls     |                                                                                                                                                                                                                           |
| Ventilation Requirements | Mechanical ventilation (dilution or local exhaust), process or personnel enclosure and control of process conditions should be provided. Supply sufficient replacement air to make up for air removed by exhaust systems. |
| Other                    | Emergency shower and eyewash should be in close proximity.                                                                                                                                                                |

## 9. Physical and chemical properties

[www.rxmarine.com](http://www.rxmarine.com)

|                     | 20% concentration                 | 30% concentration                 |
|---------------------|-----------------------------------|-----------------------------------|
| Physical State      | Liquid                            | liquid                            |
| Odor and Appearance | Clear colorless liquid. No odour. | Clear colorless liquid. No odour. |
| Odor Threshold      | 1.0 mg/m3 measured as mist        | 1.0 mg/m3 measured as mist        |

|                                    |                   |                   |
|------------------------------------|-------------------|-------------------|
| Specific Gravity (Water=1)         | ~ 1.18 at 20oC    | 1.29 at 20oC      |
| Vapor Density (Air=1)              | 3.4               | 3.4               |
| Evaporation Rate                   | Not available     | Not available     |
| Boiling Point                      | ~ 104 oC          | 113oC             |
| Freeze Point                       | ~ -23oC           | -89oC             |
| pH                                 | 12 (5% w/w)       | 12 (5% w/w)       |
| Water/Oil Distribution Coefficient | Not available     | Not applicable    |
| Density                            | 9.84              | 10.75             |
| % Volatiles by Volume              | Not applicable    | Not applicable    |
| Solubility in Water                | Miscible in water | Miscible in water |

## 10. Stability and reactivity

[www.rxmarine.com](http://www.rxmarine.com)

|                                     |                                                                                                                                                                                                                                                                                                |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Stability                           | Stable under normal conditions.                                                                                                                                                                                                                                                                |
| Incompatibility                     | Highly reactive with materials such as metals, metal oxides, hydroxides, nitrates, amines, carbonates, and other alkaline materials.                                                                                                                                                           |
| Hazardous Products of Decomposition | Toxic fumes of oxides of sulfur when heated to decomposition. Will react with water or steam to produce toxic and corrosive fumes. Reacts with carbonates to generate carbon dioxide gas, and with cyanides and sulfides to form poisonous hydrogen cyanide and hydrogen sulfide respectively. |
| Polymerization                      | Will not occur.                                                                                                                                                                                                                                                                                |

## 11. Toxicological information

[www.rxmarine.com](http://www.rxmarine.com)

|                       |                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------|
| Irritancy             | Severe irritant. Skin and eye irritant.                                                                                 |
| Sensitization         | Not available                                                                                                           |
| Chronic/Acute Effects | Not available                                                                                                           |
| Synergistic Materials | Not available                                                                                                           |
| Animal Toxicity Data  | LD50 (Oral, Rat)= 365mg/kg for Potassium Hydroxide, 210 mg/kg for Lithium Hydroxide<br>LC50 (Inhalation, Rat)= 510mg/m3 |
| Carcinogenicity       | IARC has classified "strong Alkali mists containing Potassium Hydroxide"                                                |
| Reproductive Toxicity | Investigated as a reproductive effector                                                                                 |
| Teratogenicity        | Not available                                                                                                           |
| Mutagenicity          | Investigated as a mutagen                                                                                               |

## 12. Ecological information

[www.rxmarine.com](http://www.rxmarine.com)

|               |                                                                                                                                                                                                                                                                                                                        |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fish Toxicity | LC50 Flounder (48 hr, aerated water) = 100 to 330mg/L Conditions of bioassay not specified;<br>LC50 Shrimp (48 hr, aerated water) = 80 to 90mg/L Conditions of bioassay not specified;<br>LC50 Prawn (48 hr, salt water) = 42.5ppm Conditions of bioassay not specified.<br>This material may be toxic to aquatic life |
|---------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                       |                                                                                                                                                                                                                                                                                                                 |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Biodegradability      | Not available                                                                                                                                                                                                                                                                                                   |
| Environmental Effects | When released into the soil, this material may leach into groundwater. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition. When released into the air, this material may be removed from the atmosphere to a moderate extent by dry deposition |

### 13. Disposal considerations

[www.rxmarine.com](http://www.rxmarine.com)

|                 |                                                                               |
|-----------------|-------------------------------------------------------------------------------|
| Waste Disposal: | Dispose in accordance with all federal, provincial, and/or local regulations. |
|-----------------|-------------------------------------------------------------------------------|

### 14. Transport information

[www.rxmarine.com](http://www.rxmarine.com)

|                                          |                                    |           |           |
|------------------------------------------|------------------------------------|-----------|-----------|
| GROUND - US-DOT/CAN-TDG/EU-ADR/APEC-ADR: |                                    |           |           |
| Proper Shipping Name                     | Batteries, Wet, Filled with Alkali |           |           |
| Hazard Class                             | 8                                  | ID Number | UN2796    |
| Packing Group                            | II                                 | Labels    | Corrosive |
| AIRCRAFT - ICAO-IATA:                    |                                    |           |           |
| Proper Shipping Name                     | Batteries, Wet, Filled with Acid   |           |           |
| Hazard Class                             | 8                                  | ID Number | UN2794    |
| Packing Group                            | II                                 | Labels    | Corrosive |
| Reference IATA packing instructions 870  |                                    |           |           |
| VESSEL - IMO-IMDG:                       |                                    |           |           |
| Proper Shipping Name                     | Batteries, Wet, Filled with Alkali |           |           |
| Hazard Class                             | 8                                  | ID Number | UN2794    |
| Packing Group                            | II                                 | Labels    | Corrosive |

### 15. Regulatory information

[www.rxmarine.com](http://www.rxmarine.com)

Classified as hazardous according to the criteria of NOHSC, Schedule 6 poison according to SUSDP, Class 8 according to ADG

|            |                                                                                                                                                                                                                                  |
|------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| R-phrases: | R35 Causes severe burns, and R41 Risk of Serious damage to eyes.                                                                                                                                                                 |
| S-phrases: | S2 Keep out of reach of children. S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.<br>S30 Never add water to this product. S37/39 Wear suitable gloves and eye/face protection. |

### 16. Other information

[www.rxmarine.com](http://www.rxmarine.com)

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall Rx Marine International be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if RX Marine International

has been advised of the possibility of such damages.

**DISCLAIMER OF LIABILITY :**The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

---

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.