# RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

## Material Safety Data Sheet (MSDS)

**RXSOL-60-6106-500**
Silver Nitrate Soln. LR

## 1. Product and Company Identifaction

www.rxmarine.com

| | | |
|---|---|---|
| Product Name | : | RXSOL-19-1449-025 |
| Product Type | : | TOLUENE  Pure. C6H5.CH3 |
| Chemical Family | : | Aromatic Hydrocarbon |
| Product Description | : | Clear Colourless |

**Company Details:**

RX MARINE INTERNATIONAL
105, A wing , BSEL , TECH PARK.
VASHI ,NEW BOMBAY 400703 INDIA
Stock Point ::: Kandla, Mumbai, Kolkata, Chennai, Visakhapatnam, Fujairah

| | | |
|---|---|---|
| Phone | : | +91 22 27815541 / 42 |
| Fax | : | +91 22 2781 1318 :::AOH :0091 9821214367 |
| Email | : | mail@rxmarine.com |

## 2. Composition / Information on ingredients

www.rxmarine.com

| Name | CAS# | % by Weight |
|---|---|---|
| Toluene | F, Xn, R11, R20 | 99.89 |

## 3. Hazards Identification

www.rxmarine.com

| | |
|---|---|
| Health Hazards | Harmful by Inhalation |
| Physical / Chemical And Fire Exploslon | From Flamable Mixtures. |

## 4. First Aid Measures

www.rxmarine.com

Inhalation, Skin Contact, Eye Contact, Ingestion.

## 5. Fire-fighting Measures

www.rxmarine.com

| | |
|---|---|
| Procedure | Use Water Spray To Cool Fire Exposed, Surfaces, Protect Personal, and Shut Of "Fuel" to Fire.Allow Fire To Burn Under Controlled Conditions, Extinguish With Alcohol Type Foam or Dry Chemical. Cover Liquid Spill With Foam. |

## 6. Accidental Release Measures

www.rxmarine.com

- Eliminate Ignition Sources. Prevent Liquid Enters Seawers, Water Sources, Low Area.
- Spill With Sand Earth . Dilute Contalend Spill With Water. Dispose Recover Material Conforms To local Regulation.
- Keep Public Away.

## 7. Handling and Storage

www.rxmarine.com

| | |
|---|---|
| Storage / Transport Tempreture : Amblent | Loading / Unloading Trempreture: Amblent |
| Loading / Unloading Viscosity: 0.64 | Storage / Transport Pressure: Atmospheric |
| Electrostatics Accumulation Hazards: Yes | Shipping Containers: Rall Wagons, Tanks Trucks, Tankers, Burges, Drums. |
| Materials Suitable : Carbon Steel, Stainless Still, Polyesters, Teflon. | Materials Unsuitable: Natural Rubber, Butyl Rubber, EPDM, Polyestyrene, Polyethylene, Polyproplene, Polvinyl Chloride, Polyacylonitrite. |
| - Keep Container Closed,Store Cool And Well Ventilated, Open Slowly To Control Released Pressure.<br>- Keep Away From Flame, Direct Sunlight, Store Cool And Well Ventilated.<br>- Do Not Reuse Empty Containers W/OCleaning. Obserevs all Precauations For Empty Containers. | |

## 8. Exposure controls and personal protection

www.rxmarine.com

| | |
|---|---|
| Engineering Control Measures / Ventilation | Use Local Exhaust Ventilation To Control process.Provide Mechanical Ventilation Of Confined Spaces. Use Explosion Proof Ventilation Equipment. |
| Occupational Expourse Limits (OEL) Values | TWA; 50ppm (188mg/m$^{o}$) (Skin) ACIGH (2000). |
| Personal Protection | Vapor Respirator, Gloves, Goggles, Full Suit, Footwear. |

## 9. Physical and chemical properties

www.rxmarine.com

| | | | | | |
|---|---|---|---|---|---|
| Physical State | : | Liquid | Form / Color | : | Clear Colorless |
| Odor | : | Hydcarbon Odor | Odor Threshold | : | N/A |
| Ph | : | N/A | Freezing / Melting Point | : | 95*c |
| Boiling Point Range | : | 110-111* c | Flash Point (Tcc ASTM D 56) | : | 5*c |
| Explosive Limits (In Air) | : | 1.3-6.7 vol% | Vapor Presure (38*c) | : | 7kPa |
| Auto Ignition Tempreture | : | >630* c | Density (15*c) | : | 0.865 kg / dm |
| Specific Gravity (15.0 / 15.0) | : | 0.865 | Vapour Density (101.3kPa/air=1) | : | >1.00 |

| | | | | | |
|---|---|---|---|---|---|
| Solubility In Water (25*c) | : | 0.05 WT% | Material Hydroscope | : | No |
| Viscosity (26*c) | : | 0.64cST | Evaporator Rate (n- Bu Acetate=1) | : | 2,400 |
| Coeff, Of Thermal Expansion (Liq) | : | 0.00106*c | Moiecular Weight | : | 92 |

## 10. Stability and reactivity

www.rxmarine.com

| | |
|---|---|
| Hazardous Pollymerization: No | Condition To Avoid Pollymerization : NA |
| Stability : Stable | Condition To Avoid Instability : NA |
| Materials and Conditions To Avoid: Strong Oxidizing agents<br>Hazardous Docompositions Products : None | |

## 11. Toxicological information

www.rxmarine.com

| | |
|---|---|
| Inhalation | Irritating to Eyes and Respiratory tract, diziness, central nervous System Effects.<br>Negllglble Hazard between -18*c to 38*c |
| Skin Contact | Dry Skin, Low Order Of Toxicity. |
| Eye Contact | Cause Eyes Discomfort But Will Not Injure Eye Issue. |
| Ingestion | Minimal Toxicity, Small Amounts May Cause bronchpneumonia or Pulmonary edema. |

## 12. Ecological information

www.rxmarine.com

| | |
|---|---|
| Enviromental Mobility | Highly Volatile and Will rapidly evaporate To The air If rleased Into The Water. |
| Enviromental Degradability | Biodegrade Rapidly, Remove In Wastewalar Treatment Facility. |
| Ecotoxicity and Bioaccumulation | Expected to Be Harmful to Aquatic Organisms |

## 13. Disposal considerations

www.rxmarine.com

- Combine With Other Materials To Indicate another Roule Of Disposal
- Recycle, Recover Or Dispose Empty Drums Through a Suitably Qualified Or Licenced Contractor.
- Ensure Compliance With National And Local Regulation.
- Not Suitable For Disposal eighter Landfill or via muncipal seawers, Drains , Naturals Streams or Rivers, This Product is ash less and can be burned directly in apropriate equiptment.
- Contact Local TRansmare Chemical Company Supplier Or Local Authorities for More Information.

## 14. Transport information

www.rxmarine.com

| | Land | Sea | Air |
|---|---|---|---|
| Class | 3 | 3 | 3 |
| Pg | II | II | II |

| | | | |
|---|---|---|---|
| Un Number | 1294 | 1294 | 1294 |
| Subsidlary Risk | Nil | Nil | Nil |
| Transport Document Name | Toluene, Glass3, UN 1294, PG II, (5*C c.c.) | Toluene, Glass3, UN 1294, PG II, (5*C c.c.) | Toluene |
| Others | Hazchem Code : 3YE | Marine Pollutant : No EMS Number : F-E. S-D Risk Label 3 | |

## 15. Regulatory information

www.rxmarine.com

| | |
|---|---|
| Classification And Laeling<br>Classification / Symbol : Highly Flammable / F<br>Classification / Symbol : Harmful / Xn | Governing Directive : Dangerous Substances Directive 67 / 648 / EC<br>Label Name : Toluene |
| Nature Of Special Risk:<br>R11: Highly Flammable<br>R20 Harmful By Inhalation | Safety Advise:<br>S07 / 09 : Keep Container Close & Well Ventilated.<br>S16 : Keep Away From Sourses Of Ignition.<br>S25 : Avoid Eye Contact.<br>S29 : Do Not Empty Into Drains.<br>S33 : Take Precautionary Measures Against Static Dicharges.<br>S43A :In Case Of Fire, Use Sand, Earth, Chemical Powder Alcohol Type Foam. |

## 16. Other information

www.rxmarine.com

Since 07 July 2007, This MSDS Has Been Revised In Section (s) 2, 14, 15. This Information Relateds Only To The Material Designated And May Not Be Valid For Such Information Is To The Best Of Knowledge And Belleved Accurate And Reliable As Of The Date Indicated. However, no Represention, Warranty Or Guarentee Is Made as to Its Accuary, Reliability of Completeness. It Is The User's Responsibility to satesfy himself as to the suitability and completeness of such Information for his Own Particular Use.

DISCLAIMER OF LIABILITY :The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.