



RXSOL

VARANASI CHEMICAL | RX MARINE INTERNATIONAL

Material Safety Data Sheet (MSDS)

RXSOL-81-8173-220

Water Injection Bactericide (Aldehyde Type)

1. Product and Company Identification

www.rxmarine.com

Product Name	Water Injection Bactericide (Aldehyde Type)
Product Type	RXSOL-81-8172-220

Company Details:

RX MARINE INTERNATIONAL

105, A wing , BSEL , TECH PARK.

VASHI ,NEW BOMBAY 400703 INDIA

Phone	+91 22 65113333/ 5555 / 9999 / 27611360 / 27815540
Fax	+91 22 2781 1318 ::::AOH :0091 9322594669
Email	mail@rxmarine.com

2. Composition / Information on ingredients

www.rxmarine.com

Glutaraldehyde	111-30-8	01 -10 %
Formaldehyde	50-00-0	01 - 20 %
Water	7732-18-5	To 100%

3. Hazards Identification

www.rxmarine.com

EFFECT OF OVER EXPOSURE:

EMERGENCY OVERVIEW:

Harmful if swallowed. Vapors extremely irritating to eyes & respiratory tract. This product is harmful by inhalation. When in contact with the skin and if it is swallowed.

EYE CONTACT:

This product is severely irritating to the eyes & may cause irreversible damage including burns & blindness. Symptoms may include stinging, tearing, redness, swelling & blurred vision.

SKIN CONTACT:

Corrosive to the skin contact with the skin or mucous. Membranes may cause severe irritation & burns. This product contains a component that may cause allergic skin reactions

SKIN ABSORPTION:

A component in this product may be absorbed through the skin, especially if skin is damaged.

INHALATION:

This product may cause irritation to the respiratory system. Repeated inhalation may be harmful, lung irritation & serious central nervous system disorders may result. Excessive inhalation of this material cause headache, dizziness, nausea & in coordination. Primary route (s) of entry% inhalation, ingestion, eye contact.

INGESTION:

This product may produce corrosive damage to the gastrointestinal tract if it is swallowed. This may be harmful of fatal if swallowed.

4. First Aid Measureswww.rxmarine.com**EYE CONTACT:**

Immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get Medical attention, if irritation persists.

SKIN CONTACT:

Immediately wash Skin with soap and water. Get Medical attention, if irritation persists

INHALATION:

Remove to fresh Air. If not breathing, give artificial respiration. If breathing is difficult, give Oxygen. Get immediate medical attention, if symptoms persist.

INGESTION:

If swallowed induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately

5. Fire-fighting Measureswww.rxmarine.com

Flash Point	: MORE THAN 100° C (Closed Cup)
Lower Explosive Limit	: N.D.
Upper	: N.D.
Auto Ignition Temp	: N.D.

Unusual Fire or Explosion Hazard :

Vapors can travel to a source of ignition and flash back. Combustible Liquid “Empty” containers retain product residue (Hard and / or vapor) and can be dangerous. Do not Pressurize, Cut, Weld Braze, Solder, Drill, grind, or expose such containers to heat, flame, Sparks or other sources of ignition. They may explode and cause injury or death.

Decomposition products: Irritating & toxic gases or fumes may be released during a fire.

Extinguishing Media:

Dry chemical foam Carbon Dioxide, water may be an ineffective extinguishing medium. Use water to cool fire exposed containers & to protect personnel.

Fire-Fighting instructions:

Firefighters should wear full protective clothing including self contained breathing apparatus.

6. Accidental Release Measureswww.rxmarine.com**CONTAINMENT PROCEDURES:**

Stop the flow of material, if this is without risk. Eliminate all sources of ignition. Or flammable that may come in to contact with a spill of this material. Wear appropriate protective equipment & clothing during clean-up

CLEAN-UP PROCEDURES:

Absorb spill with absorbent pad, inert material shovel material in to appropriate container for disposal. Dispose of collected material according to regulation. Ventilate the contaminated area.

7. Handling and Storagewww.rxmarine.com**HANDLING PROCEDURES:**

Do not allow contact with eyes. Avoid getting this material into contact with your skin. Wash thoroughly after handling. Avoid breathing vapors or mists of this product. Do not take internally for industrially use only. Keep this product away from heat, sparks or open flame.

STORAGE PROCEDURES:

Keep Container tightly closed & in a cool, well-ventilated place away from in compatible materials. Eliminate all sources of ignition.

8. Exposure controls and personal protectionwww.rxmarine.com**ENGINEERING CONTROL:**

Local exhaust ventilation may be necessary to control any air contaminants to within their TLVS during the use of this products. Facilities storing or utilizing this material should be

equipped with an eye wash facility and a safety shower

PERSONAL PROTECTIVE EQUIPMENT:

As prescribed in the OSHA standard for personal protective equipment employers must perform a hazard assessment of all workplaces to determine the need for & selection of proper protective equipment for each task performed.

EYES/FACE PROTECTIVE EQUIPMENT:

Wear chemicals goggles. Face shield [if splashing is possible]

SKIN PROTECTION:

Use impervious gloves, gloves should be tested to determine suitability for prolonged contact. Use of impervious apron & boots are recommended.

RESPIRATORY PROTECTION:

If ventilation is not sufficient to effectively prevent buildup of aerosols or vapors, appropriate NIOSH / MSHA respiratory protection must be provided.

WORK PRACTICES:

Eye wash fountain & emergency showers are recommended.

9. Physical and chemical properties

www.rxmarine.com

Physical State	:Homogeneous Liquid
Appearance	:Colourless to Pale Yellow Liquid
Vapor Pressure	:Not Determined
Vapor Density	:Not Determined
Specific Gravity	:1.00 ± 0.05 gm/ml at 25° C
Boiling Point	:Not Determined
Viscosity	:< 100 CST at 25° C
Solubility in Water	:Soluble
Percent Volatile	:Not Determined
pH (Value)	:3.0 to 10.0
Pour Point	:Below 0° C

10. Stability and reactivity

www.rxmarine.com

Chemical Stability : Stable under normal condition

Conditions to avoid :Keep away from heat, ignition sources & in compatible.

Incompatibilities :

This product may react with strong oxidizing agents. This product may react with reducing agent. This product may react with strong alkalis.

Decomposing Product :

Upon decomposition this product may yield oxides of nitrogen & ammonia, carbon dioxide, carbon mono oxide & other low molecular weight hydrocarbons.

Hazardous polymerization :will not occur

11. Toxicological information

www.rxmarine.com

HEALTH EFFECTS: Acute:

Ingestion:

This product is considered to be harmful if swallowed. Ingestion effects may include headache, nausea, vomiting, abdominal pain and central nervous system depression.

Skin: Harmful in contact with skin. May cause moderate to severe irritation.

Eyes: Liquid contact with the eyes can cause severe irritation.

Inhalation:

Harmful by inhalation. Inhalation of vapour may cause respiratory irritation, headache, dizziness, drowsiness and loss of co-ordination.

Chronic:

Repeated or prolonged skin contact may cause defatting of the skin and lead to dermatitis. Frequent or prolonged inhalation exposure may result in liver and kidney disorders.

12. Ecological information

www.rxmarine.com

ECOTOXICITY	: DATA NOT AVAILABLE
ENVIRONMENTAL FATE	: DATA NOT AVAILABLE
SOIL ABSORPTION/ MOBILITY	: DATA NOT AVAILABLE

13. Disposal considerations

www.rxmarine.com

Consult local, state or federal regulatory agencies for acceptable disposal procedures, & disposal, locations. Disposal in streams or sewers may be prohibited by federal, state & local

regulations.

14. Transport information

www.rxmarine.com

DOT TRANSPORTATION DATA:

PROPER SHIPPING NAME :

Corrosive Liquid, Basic, Organic N.O.S. (Quaternary Ammonium Compounds)

UN No. :	: 3265
Class :	: 8
PACKING GROUP	: II

15. Regulatory information

www.rxmarine.com

US FEDERAL REGULATIONS:

As follows OSHA: Hazardous by definition of hazard communication standard (29CFR 1910.1200)

CERCLA-SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA' hazard categories promulgated under Sections 311 & 312 of superfund amendment & reauthorization act of 1986 (SARA title III) is Considered, under applicable definitions, to meet the following categories.

- * Immediate health hazard
- * Chronic health hazard
- * Fire hazard

16. Other information

www.rxmarine.com

The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents. The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties. The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications; usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.

DISCLAIMER OF LIABILITY : The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as

a component in another product, this MSDS information may not be applicable.

This Safety Data Sheet is provided by RXSOL. For the most current version of this document, please visit **varanasichemical.com**. This document is prepared in accordance with GHS / OSHA HazCom standards. The information contained herein is believed to be accurate but does not purport to be all-inclusive. It is the responsibility of the user to determine the suitability of this information for their application.